Integrated Developme	ent Assessment System form		
	Hosamen		
Application Details - IDA	<b>4S form 1</b>		
(Sustainable Planning Act 2009 version 1.0 effective 18 Decem	nber 2009) ( 3 · 0 APR 2010 )		
You MUST complete ALL questions unless the for necessary information and documentation will resu	m indicates otherwise. Incomplete folgris or forms without all it in your application not being a properly grade application.		
For all development applications, you must:	REGIONAL		
complete this form (Application details - IDAS	S form 1)		
complete any other forms relevant to your ap	plication		
<ul> <li>provide any mandatory supporting information application.</li> </ul>	n identified on the forms as being required to accompany your		
All terms used on this form have the meaning give Planning Regulation 2009.	en in the Sustainable Planning Act 2009 or the Sustainable		
correct. Any development permit or preliminary apple issued to the applicant.)	ensuring the information provided on all IDAS application forms is proval that may be issued as a consequence of this application will provide additional applicant details by clicking the "Add another		
Name/s (individual or company name in full)	Town & Country LTD		
For companies, contact name	Mr Stuart Lovell		
Postal address	PO Box 100 Mossman Q 4873		
Contact phone number	4084 1800		
Mobile number (non-mandatory)			
Fax number (non-mandatory)	4098 2233		
e-mail address (non-mandatory)			
1. What is the nature of development proposed	? (tick all applicable boxes)		



material change of use of premises

□ building work☑ operational work□ reconfiguring a lot

2. Wha	t typ	e of a	pprova	l is being :	sought?					
br	development permit preliminary approval both - provide details below									
3. Is th	e ap	plicat	ion for	a mobile a	nd tempora	ary enviro	nmenta	illy relev	ant activity (E	ERA)?
	<del>2</del> \$ - (	·			n go to ques					
4. Loca	ation	of the	e premi	ses (comp	lete table B	and/or tab	le C as	applicab	e. Identify eac	h lot in a separate row)
Table I premise		treet a	ddress/I	ot for the p	remises or	street addr	ess/lot	on plan f	or the land adj	oining or adjacent to the
		Stree	et Addre	ess					t on plan scription	Local government area
		Unit No.	Street No.		name and or name and or name		Post code	Lot No.	Plan type and plan no.	(e.g. Logan,Cairns)
	1		63	Front Stre	et, Mossma	an	4873	101	SP186233	CRC
Stre wate	et ad er e.g	ddress g. jetty remise	, pontoc s coord	plan for the	-					riate for development in of a lot or in water e.g.
		coord	inates ir	n a separat			— ref	Zone erence	Datum	Local government area (If applicable)
	Easting Northing Latitude Longitude   reference   area (if applicable)   GDA94   WGS84   other									
5. Tota	l are	a of t	ne prem	ises on w	hich the de	velopmen	t is pro	posed (	indicate hectar	res or m²)
2.38 h										
6. Curr	6. Current use/s of the premises (e.g. vacant land, house, apartment building, cane farm, etc.)									
	1 Vacant									
7. Prov	ide (	a brie	f descri	ption of th	e proposal	(e.g. six u	nit apai	tment bu	ilding, 30 lot re	esidential subdivision etc.)
Comme	Commercial Development									

8. Is owner's consent required for this application? (refer to notes at the end of this form for more information)						
☑ No ☑ Yes - complete either table D, table E or table F as applicable						
9. Does the application involve a state resource? (e.g. the application involves state land, or takin materials. Refer to the notes at the end of this form for more information)	ng quarry					
10. Identify if any of the following apply to the premises (tick applicable box/es)						
adjacent to a water body, watercourse or aquifer (e.g creek, river, lake, canal) - complete table	e H					
on strategic port land under the Transport Infrastructure Act 1994 - complete table I						
in a tidal water area - complete table J						
11. Are there any existing easements on the premises? (e.g. for vehicular access, electricity, over water, etc.)	erland flow,					
☑ No ☐ Yes - ensure the type, location and dimension of each easement is included in the plans	submitted					
12. Does the proposal include new building work or operational work on the premises? (include services)	ding any					
☐ No ☑ Yes - ensure the nature, location and dimensions of proposed works are included in plan	s submitted					
13. Is the payment of a portable long service leave levy applicable to this application? (refer to end of this form for more information)	o the notes at the					
☐ No - Go to question 15 ☐ Yes						
15. Has the local government agreed to apply a superseded planning scheme to this application under section 96 of the Sustainable Planning Act 2009?						
No Yes - provide details below						
16. List below all of the forms and supporting information that accompany this application (include all IDAS forms, checklists, mandatory supporting information etc. that will be submitted as part of this application. Note: this question does not apply for applications made online using Smart eDA)						
t Description of attachment of title of attachment t	of lodgement to sment manager					
1						
17. Applicant's declaration						
By making this application, I declare that all information in this application is true and correct (note: it is unlawful to provide false or misleading information).						

•							
Notes for completing this form							
for an application. Section 260(1)(e) of the Susta required under section 263, then an application r	Section 263 of the Sustainable Planning Act 2009 sets out when the consent of the owner of the land is required for an application. Section 260(1)(e) of the Sustainable Planning Act 2009 provides that if the owner's consent is required under section 263, then an application must contain, or be accompanied by, the written consent of the owner, or include a declaration by the applicant that the owner has given written consent to the making of the application.						
<ul> <li>Question 9:</li> <li>Section 264 of the Sustainable Planning Act 200 regulation may require the application to be supposed Schedule 14 of the Sustainable Planning Regular required to be given, and the evidence required,</li> </ul>	ported by certain evidention 2009 prescribes	dence prescribed under the state resources for	er the regulation.				
<ul> <li>Question 13:</li> <li>The Building and Construction Industry (Portable long service leave levy is payable.</li> <li>The portable long service leave levy amount and are prescribed in the Building and Construction In</li> </ul>	d other prescribed pe	ercentages and rates f	or calculating the levy				
<ul> <li>Construction Industry (Portable Long Service Leapermit is issued.</li> <li>Building and Construction Industry Notification at office or agency, on request from QLeave, or care</li> </ul>	<ul> <li>The portable long service leave levy need not be paid when the application is made, but the Building and Construction Industry (Portable Long Service Leave) Act 1991 requires the levy to be paid before a development permit is issued.</li> </ul>						
<b>Privacy</b> -the information collected in this form will be used by the Department of Infrastructure and Planning (DIP) in accordance with the processing and assessment of your application. Your personal details will not be disclosed for a purpose outside of the IDAS process, except where required by legislation (including the <i>Right to Information Act 2009</i> ) or as required by Parliament. This information may be stored in a departmental database. The information collected will be retained as required by the <i>Public Records Act 2002</i> .							
OFFICE USE ONLY							
Date received Reference numbers							
NOTIFICATION OF ENGAGEMENT OF A PRIVATE CERTIFIER							
To:		en engaged as the priv red to in this application					
Date of engagement Name		BSA Certification license number	Building classification/s				

	Description of the work	QLeave Project Number	Amount paid (\$)	Date paid	Date receipted form sighted by assessment manager	Name of officer who sighted the form
1						

QLEAVE NOTIFICATION AND PAYMENT (for completion by assessment manager or private certifier if applicable)

The Sustainable Planning Act 2009 (SPA) is administered by the Department of Infrastructure and Planning. This form and all other required application materials should be sent to your assessment manager and any referral agencies.





# Building or operational work assessable against a planning scheme - IDAS form 6

(Sustainable Planning Act 2009 version 1.0 effective 18 December 2009)

This form must be completed for development applications for building works or operational work assessable against a planning scheme.

You **MUST** complete **ALL** questions unless the form indicates otherwise. Incomplete forms or forms without all necessary information and documentation will result in your application not being a properly made application.

For all development applications, you must:

- complete Applicant details IDAS form 1
- complete any other forms relevant to your application
- provide any mandatory supporting information identified on the forms as being required to accompany your application.

All terms used on this form have the meaning given in the Sustainable Planning Act 2009 or the Sustainable Planning Regulation 2009.

This form can also be used for development on strategic portland under the Transport Infrastructure Act 1994.

1. What is the nature of the work that requires assessment against a planning scheme? (tick applicable box/es)				
building work - complete table A	☑ operational work - complete table B			
Table B				
What is the nature of the opera	ational work made assessable in the planning scheme? (tick applicable box/es			
road works	stormwater			
☑ drainage Works	earthworks 🔀 sewerage infrastructure			
landscaping s	signage			
other - please specify below	w			
	sought? (if you have indicated multiple works in the above question, please to detail each approval request)			
development permit	preliminary approval both - specify below			
is the operational work necessa	ary to facilitate the creation of new lots? (e.g. subdivision)			
No	he number of lots being created			
Are there any current approvals	s associated with this application? (e.g. material change of use)			
☐ No ☐ Yes - provide o	details below			



	List of approval reference/s	Date approved	Date approval lapses			
1	MW 8/38/2	12 MAY 2009	12 MAY 2013			

1				$\neg$
	2. What is the dollar value of the proposed building work? (inc GST, materials and labour)	\$	NIG	- 1
١		•	-444.	- [

_			
3.	Confirm the following mandatory supporting information accompan	ies this applica	ition
		Confirmation of lodgement	Method of lodgement
ΑĪ	applications for operational works		
sit	e plans drawn to scale which show the following:		
•	the location and site area of the land to which the application relates (relevant land) the north point		
•	the boundaries of the relevant land		
•	the allotment layout showing existing lots, any proposed lots (including the dimensions of those lots), existing or proposed road reserves, building envelopes and existing or proposed open space (note: numbering is required for all lots)	confirmed	over the counter
•	any existing or proposed easements on the relevant land and their function		
•	any access limitation strips		
•	all existing and proposed roads and access points on the relevant land		
go	statement about how the proposed development addresses the local overnment's planning schemes and any other planning documents levant to the application	⊠ confirmed	over the counter
Αį	oplications for operational works involving earthworks (filling and e	xcavating)	
dr.	awings showing:		
•	existing and proposed contours areas to be cut and filled the location and level of any permanent survey marks or reference	confirmed	
•	stations used as datum for the works the location of any proposed retaining walls on the relevant land and their height the defined flood level (if applicable)	conmined	
•_	the defined fill level (if applicable)		
Δı	oplications for operational works involving roadworks		<u> </u>
dr	awings showing:		•
•	existing and proposed contours the centreline or construction line showing chainages, bearings, offsets if the construction line is not the centreline of the road and all intersection points		
•	information for each curve including tangent point chainages and offsets, curve radii, arc length, tangent length, superelevation (if applicable) and curve widening (if applicable)		
•	kerb lines including kerb radii (where not parallel to centreline) and tangent point changes (where not parallel to centreline)		
•	edge of pavement where kerb is not constructed	confirmed	
•	position and extent of channelisation location and details of all traffic signs, guideposts, guardrail and other		
٦	street furniture		
	pavement markings including details on raised pavement markers		
•	catchpit, manhole and pipeline locations		
•	drainage details (if applicable)		
•	cross road drainage culverts (if applicable)	1	
•	concrete footpaths and cycle paths	1	
	location and details for access points, ramps and invert crossings changes in surfacing material		

L			
:		Confirmation of lodgement	Method of lodgement
A	oplications for operational works involving stormwater drainage	•	
•	awings showing:  existing and proposed contours  drainage locations, diameters and class of pipe, open drains and easements  manhole location, chainage and offset or co-ordinates and inlet and outlet invert levels inlet pit locations, chainage and offset or co-ordinates and invert and kerb levels		over the counter
A)	oplications for operational works involving water reticulation		
di	awings showing:  kerb lines or edge of pavement where kerb is not constructed location and levels of other utility services where affected by water reticulation works pipe diameter, type of pipe and pipe alignment water main alignments water supply pump station details (if applicable) minor reservoir details (if applicable) conduits location of valves and fire hydrants location of house connections (if applicable) location of bench marks and reference pegs	confirmed	over the counter
A	oplications for operational works involving sewerage reticulation		
	location of all existing and proposed services location of all existing and proposed sewer lines and manhole locations location of all house connection branches kerb lines or edge of pavement where kerb is not constructed chainages design sewer invert levels design top of manhole levels type of manhole and manhole cover pipe diameter, type of pipe and pipe alignment location of house connections (if applicable) sewer pump station details (if applicable)	<b></b> ✓confirmed	over the counter
Α	oplications for operational works involving street lighting		
dr • •	awings showing: location of all light poles and service conduits location of all other cross road conduits type of wattage and lighting any traffic calming devices additional plans for roundabouts and major roads (if applicable) details of any variations to normal alignment details of lighting levels	confirmed	

	Confirmation of lodgement	Method of lodgemen
Applications for operational works involving public utility services	<u>l</u>	
drawings showing:  any existing light poles and power poles  any existing underground services  details of proposed services  alternation to existing services	confirmed	
Applications for operational works involving landscaping works		
the location of proposed plant species a plant schedule indicating common and botanical names, pot sizes and numbers of plants planting bed preparation details including topsoil depth, subgrade preparation, mulch type and depth, type of turf, pebble, paving and garden edge the location and type of any existing trees to be retained construction details of planter boxes, retaining walls and fences the proposed maintenance period irrigation system details	confirmed	
Notes for completing this form:  This form can also be used for development applications for building wagainst the land use plan for Cairns airport land or Mackay airport land mentioned, take it to mean the land use plan for the airport land.  Privacy -please refer to your assessment manager for further details this form.	d. Whenever a pla	anning scheme is
OFFICE USE ONLY		
Date Received Reference Numbers		

all other required application materials should be sent to your assessment manager and any referral agencies.

# **GMA Certification Group Pty Ltd**

### **BUILDING SURVEYORS**

# Queensland's leaders in Building Certification Services



PORT DOUGLAS OFFICE

PHONE: (07) 4098 5150 FAX: (07) 4098 5180

Let 9 Unit 5 Craiglie Business Park Owen Street CRAIGLIE QLD 4877

POSTAL: P.O. Box 831, PORT DOUGLAS QLD 4877

E-Mail: adminin@geoffmitchell.com.au Web: <u>www.geoffmitchell.com.au</u>

18 April 2010

Cairns Regional Council PO Box 359 CAIRNS Q 4870

Attention:

**Development Assessment** 

Dear Sir.

Re: Operational Works Application

Mossman Gateway Shopping Centre

Lot 101 SP186233 Front Street, Mossman

GMA Certification Group Pty Ltd has been engaged to provide building certification services for the above project. Additionally, the owner has requested we submit the Operational Works application on their behalf.

Accordingly, please find enclosed an application for Operational Works for the abovementioned property, which includes:

- 1. IDAS Forms 1 & 6
- 2. Copies of plans including an electronic copy on disc
- 3. Geotechnical report
- 4. Statement of Compliance, and,
- 5. 1 x copy of MCU approval

Please advise the schedule fee for the application.

Should you require any further information or wish to discuss the application, please contact me on 4098 5150 or by email <u>ievans@gmacert.com.au</u>

Kind Regards,

GMA Certification Group P/L

Encl.



# GILBOY HYDRAULIC SOLUTIONS

GJ & TL GILBOY PTY LTD / ACN: 105 215 432 / ABN: 85 105 215 432

4/131 Scott Street, Bungalow. Phone: (07) 4051 5116 Fax: (07) 4051 5016 Mobile: 0439 664623 Email: greg@gilboy.com.au

### FIRE HYDRANT FLOW AND PRESSURE TEST CERTIFICATE

PROPERTY LOCATION:	TOWN & COUNTRY SHOPPING CENTRE CARPARK,
	FRONT STREET, MOSSMAN
HYDRANT LOCATION NO: 3	DUAL HEADED ABOVE GROUND HYDRANT IN LANDSCAPING OF TOWN & COUNTRY SHOPPING CENTRE, MOSSMAN
SIZE OF MAIN:	Assumed 100mm diameter
TEST CONDUCTED FOR:	LINCOLNE SCOTT - BRISBANE
DATE:	19 <sup>th</sup> June 2009
TIME:	12.00 pm
TESTA	ČESULTS
FIRE HYDRANT NO: 3	DUAL HEADED ABOVE GROUND HYDRANT
	IN LANDSCAPING OF TOWN & COUNTRY SHOPPING CENTRE, MOSSMAN
STATIC PRESSURE:	850 KPa
FLOW RATE ACHIEVED WITH 1 HYDRANT	Full Flow = 30 Litres/second
OPERATING:	Residual Pressure @ 20 lit/sec = 600 Kpa
	Residual Pressure @ 10 lit/sec = 750 KPa

Comments:	 	

Name of Person Signing: Gregory Gilboy A.H.S.C.A. Certificate No: 48 / F.P.C.R.B.Q No. 1262

Position: Manager

19th June 2009 Signature: Date:



ENQUIRIES: PHONE:

Luke Jackson (07) 4044 3240 (07) 4044 3836

FAX: YOUR REF:

62830/BCS/NAC/L65095

OUR REF:

8/38/2 (2051791)

12 May 2009

Town & Country Limited C/- CONICS Pty Ltd PO BOX 355 MOSSMAN QLD 4873

11 5 MAY 2003

Dear Sir/Madam

# <u>DECISION NOTICE TO CHANGE AN EXISTING APPROVAL FOR</u> <u>DEVELOPMENT APPLICATION FOR 63 FRONT STREET MOSSMAN</u>

With reference to the above request to Change an Existing Approval, please find attached the relevant Decision Notice which was determined under Instrument of Delegation on 12 May 2009.

The notice includes extracts from the Act with respect to making representations about conditions, negotiated decisions, suspension of the appeal period, and lodging an Appeal.

Should you have any enquires in relation to this Decision Notice, please contact Luke Jackson of Council's Development Assessment Team on telephone number (07) 4044 3240.

Yours faithfully

Simon Clarke

Manager Development Assessment

Att.

40.2009.3102 1/19



#### **APPLICANT DETAILS**

Town & Country Limited C/- Conics Pty Ltd PO BOX 355 MOSSMAN QLD 4870

#### **ADDRESS**

63 Front Street MOSSMAN

#### REAL PROPERTY DESCRIPTION

Lot 101 on SP186233

#### **PROPOSAL**

Shopping Facilities& Business Facilities - Request for Minor Change to Conditions of Approval

#### **DECISION**

Approved subject to conditions (refer to approval package below).

#### **DECISION DATE**

12 May 2009

#### **TYPE**

Material Change of Use (Development Permit)

#### **REFERRAL AGENCIES**

Department of Main Roads Cairns District PO Box 6185 CAIRNS QLD 4870

#### SUBMISSIONS .

There were no submissions for this application.

### **FURTHER DEVELOPMENT PERMITS REQUIRED**

Development Permit for Building Works
Development Permit for Plumbing Works
Development Permit for Operational Works

# CODES TO COMPLY WITH FOR SELF-ASSESSABLE DEVELOPMENT None

40.2009.3102 2/19

DOES THE ASSESSMENT MANAGER CONSIDER THE APPLICATION TO BE IN CONFLICT WITH APPLICABLE CODES, PLANNING SCHEME, STATE PLANNING POLICIES OR PRIORITY INFRASTRUCTURE PLAN (IF YES, INCLUDE STATEMENT OF REASONS)

Not in conflict

That Council approve the development application for a Material Change of Use (Code) for the purpose of Shopping Facilities and Business Facilities over land described as Lot 101 SP186233, located at 63 Front Street, Mossman, subject to the following conditions:

1. That Condition 1 be amended to read as follows:

### Plan of Development



The approved development and the conduct of the approved use, the carrying out of any works on the premises and the construction of any buildings on the premises associated with the development must generally be in accordance with the details of the application and the following approved Plan/s of Development:

Title	Plan No.	Date
Site Plan Proposed Site Plan	CO650 DA01	<del>Jan-2007</del> <u>Jan</u>
	07125-DA100B	2009
Elevations	CO650	<del>Jan 2007</del>
Proposed Elevations	<u>07125 – DA101B</u>	<u>Jan 2009</u>
Main Roads Concept Layout	GCS06 - 194	06/05/07
DMR Option Concept Layout	GCS06 - 194	06/05/07

Except where such plans are modified by the terms of this approval.



That Condition 14 be amended to read as follows:

#### Car Parking

- 14. A Car parking area with a minimum of three hundred and thirty (330) spaces two hundred and eighty-five (285) shall be constructed, sealed, drained and line marked in accordance with the relevant Australian Standard and the approved plan of development and maintained thereafter.
- 3. That condition 15 be deleted.
- 4. All other conditions of the Decision Notice approved by Council on 8 August 2007 remain unchanged.


Note:


This decision does not include the proposed licensed dining area which requires a separate development assessment.

**RIGHTS OF APPEAL** 

Attached

**End of Decision Notice** 





### Appendix 2

Mrs Natalie Clark -- Planning Officer Planning Services Section - **2** (07) 4099 9456 planning@dsc.qld.pov.au MCUC 007/07

Town & Country Limited C/- Jemny Elphinstone Pty Ltd PO Box 1098 MOSSMAN QLD 4873

8 August 2007

# INTEGRATED PLANNING ACT DECISION NOTICE

### DEVELOPMENT APPLICATION

Applicant's Name

: Town & Country Limited

Owner's Name

: Town & Country Limited

Proposal

Material Change of Use for the purpose of Shopping

Facilities and Business Facilities

Application Number

MCUC 007/07

Site Address

63 Front Street, Mossman

Property Description

Lot 101 on SP186233, Parish of Victory, County of Solander

A. Decision:

Decision Date: 2 August 2007

Approved subject to Conditions

B. Type of Development Approval:

Material Change of Use

Development Permit

.../2.

-2-

### C. Referral Agency:

Department of Main Roads Peninsular District PO Box 6185 CAIRNS QLD 4870

#### D. Conditions

#### Plan of Development

The approved development and the conduct of the approved use, the carrying out
of any works on the premises and the construction of any buildings on the
premises associated with the development must generally be in accordance with
the details of the application and the following approved Plan's of Development:

Title	Plan No.	Date	
Site Plan	CO650 - DA 01	Jan 2007	
Elevations	CO650	Jan 2007	
Main Roads Concept Layout	GCS06 - 194	06/05/07	
DMR Option Concept Layout	GCS06 - 194	06/05/07	

Except where such plans are modified by the terms of this approval.

#### Currency Period

This development approval lapses four (4) years after the day that the development approval takes effect, unless extended under Section 3.5.22 of the Integrated Planning Act 1997.

#### Landscaping

- The following amendments are to be made to the landscaping plan, titled Landscape Concept Planting Design, numbered LCPP-0001 and dated 7 Feb 2007, submitted with the proposed development:
  - (a) The landscaping area along the rear western boundary is to be increased to 1.5 m wide to allow for dense screening vegetation;
  - (b) Golden Penda's or a similar native shade tree is to be incorporated into the landscaped area along the road frontage at 4 metre centres to provide shade to the car parking area directly adjacent.

.../3.

-3-

The amended plantis to be submitted to Council prior to obtaining a building permit/operational works permit.

A Landscaping Maintenance Schedule for a period of three (3) years is to be provided to Council with the amended landscaping plan. The Maintenance Schedule is to be accompanied by a \$10,000.00 performance bond. The bond is refundable at the completion of the scheduled period on the provision the landscaping is established and maintained in accordance with the Schedule.

5. The owner/developer shall be responsible for all maintenance work for a period of three (3) years. Council will not accept the landscaping off maintenance until it meets the requirements of Council's Engineering Services.

Irrigation for external landscaping shall be transferred to Council's reticulated water system prior to landscaping being accepted as off maintenance.

#### Water Supply

7. The plans and specifications of the internal water supply must be submitted to Council at Operational Works application stage for this development for review.

This system must make provision for services to the boundaries of all lots, including main works; enveloper pipes at cross street services and valve and hydrant markers and be designed in accordance with the requirements of Planning Policy No.6 "Planning Scheme Policy No.6 "FNQROC Development Manual".

#### Sewerage

No additional external structural loads are permitted to be applied to Council's existing sewer as a consequence of the approved development. Plans and specifications for the internal sewer and connection to Council's sewerage system are to be submitted to Council with the application for Operational Works.

#### **Electricity and Telephone Services**

All electrical lines along the full frontages of the subject site (Front Street) are to be placed underground. These works are to be undertaken by Ergon Energy at the developers/owners expense and are to be completed prior to commencement of the approved use.

.../4.

4.

#### Stormwater

- 10. All stormwater run-off from non-permeable surfaces and roof areas occurring on the site must be collected within the premises and discharged to the legal and practical point of discharge which has been nominated as Front Street. The applicant is required to extend the existing underground stormwater (from the existing surge pit located adjacent current entrance) for the full frontage of the allotment. In addition the applicant is to extend the existing kerb and channel for the full frontage of the allotment and undertake the necessary widening of Front Street. Plans and specifications for the control of stormwater (including design of discharge outlet, layout of kerb and channel and widening of Front Street) must be submitted to Council with the application for Operational Works. The approved use must not:
  - a) Interfere with the natural flow of stormwater;
  - b) Cause ponding of stormwater on adjoining properties.

H

The developer/owner is required to place pollution control devices in stormwater drains in accordance with the requirements of Planning Policy No.6 "Planning Scheme Policy No.6 "FNQROC Development Manual". The design and location of these devices must be submitted at Operational Works application stage.

#### Contributions



The developer/owner shall pay to the Council headworks contributions for water supply and sewerage in accordance with Council's Planning Scheme Policy No. 11 – Water Supply and Sewerage Headworks and Works External Contributions (The Policy). The contribution shall be calculated at the rate per Equivalent Domestic Connection (EDC) applicable at the time of payment in accordance with the policy.

The current number of EDC's for the approved use are:

Water Supply 21.8 Sewerage 21.8

.../5.

-5-

#### Flooding and Drainage



Plans of the filling and excavation are to be designed in accordance with the FNQROC Development Manual and be submitted at Building Work stage and must not:

- (a) Pond water on the site, adjacent site or impact on the adjacent Statecontrolled road;
- (b) Result in an increase in the flow of water across a site or any other land or the adjacent State-controlled road; and
- (c) In an increase in the volume of water or concentration of water in a watercourse and overland flow paths;

#### Car parking



A car parking area with a minimum of three hundred and thirty (330) spaces shall be constructed, sealed, drained and line marked in accordance with the relevant Australian Standard and the approved plan of development and maintained thereafter.



The developer/owner is to provide an amended plan of development prior to obtaining a Building Permit, showing nine (9) designated Disabled Car Parking spaces in accordance with the provisions of the Douglas Shire Planning Scheme.

#### Refuse



There is to be provided within the development an area for the storage and washing of all refuse containers in accordance with the *Environmental protection* (Interim Waste) Regulation 1996. Such area is to be:

- sufficient in size to be able to house all mobile garbage (wheelie) bins including recycling bins
- situated so as not to cause an odour nuisance to any adjacent properties:
   and
- c) imperviously paved and drained to a suitable slit trap; and
- d) discharged to sewer to the satisfaction of the General Manager Engineering Services; and
- e) provided with a suitable hose cock with backflow prevention device and hose; and
- f) roofed or provided with a suitable automatic diversion valve (or other approved method) designed to prevent the ingress of stormwater to sewer.

.../6.

-6-

#### Advertising Devices



The developer/owner is to provide each Business/Shopping Facility with a blank "Below Awning Sign" with the following dimensions:

- (a) Maximum height of 0.6 metres;
- (b) Maximum width of 0.3 metres;
- (c) Maximum length of 2.5 metres and does not project beyond the awning.

The blank sign can then be designed by the occupant of the facility when confirmed.

#### **Environmental Management Plan**



The Developer is to submit with the application for approval of Operational Works, an Environmental Management Plan (EMP) in accordance with the requirements of Planning Scheme Policy No.10 "Reports and Information the Council may Request". This EMP must detail the controls to be utilised to ensure that no environmental harm or muisance is caused from the construction of the works and must include a Stormwater Management Plan.

#### Compliance



All conditions shall be complied with prior to the occupancy of the building for the approved use or commencement of the approved use on the land. Any developer security, associated with this approval will not be released until all conditions of approval are complied with.

#### Security

21. To guarantee the satisfactory completion of the landscaping and to ensure payment of headworks contributions, the developer shall lodge with the Council a Cash Bond or Guarantee to the value of \$194,957.00. Such guarantee shall be lodged prior to the issue of a Building Work Permit. The Council may call up this Guarantee to complete all or any part of the works mentioned herein in accordance with the conditions of this approval, should the developer fail to do so prior to issuing a permit for Building Work.

.../7.

40.2009,3102

-7-

#### Advice


Should any future business wish to utilise a Chalk Board or A Frame Advertising Device; registration is required through Council's Environmental Health Services.


An application for an Operational Works Permit for an Advertising Device will be required to be submitted and approved by Council prior to the installation of any proposed Tenancy Sign or other advertising sign assessable against the Planning Scheme.

### E. Further Development Approvals Required:


Operational Work Building Permit Development Permit Development Permit

Paul Trotman General Manager – Development & Environment





#### Appendix B - Department of Main Roads conditions



Dear Ma Len

(:

(

Dengies Shire: Capitale Cook Highway (Front Street)
Streeted at Testa & Country Shopping Cantre, Frent Street, Masterna
Let 101 on 37-13cint, Parish of Victory
Tosse & Country Limited
Proposed Meterial Cantre of Use (Shopping Enclides & Basiness Enclides) Application
Concurrence Agency's Response (conditions apply)

Levier to the above application received at the Department 15 Fahreary 2007, 20 Pebruary 2007 and 11 May 2007 regressing condensation of the above development.

#### A. CONDITIONS OF DEVELOPMENT

Pursuant to the Enterprised Planning Act 1997, the Quantum Department of Main Roads, as a Communication Agency, has assessed the Impact of the proposed development on the State-controlled road network and requires that Commit include the following conditions of development for the subject applications:

#### Permitted Read Access Lucation

- (i) Ances between Front Street and the proposed development shall be vis:

   the existing access located apposite the Harper farest betweenism, and

   a new screen located at the southern side boundary of the subject had.
- (ii) No additional direct across between Front Street and the proposed development is permitted.

#### Rend Access Wethe

- (i) Read access works at the paratited road access locations are required, and shall be constructed in accordance with:

  the Department of Mirth Roads Road Planning and Design Mount and
  extract Department of Main Roads standards.

Coline Corperate Toron, 15 Lake Break Commercial 4610

-2-

A recent tile inspection indicates that the required road access works are as follower.

a channelled right turn breatment (CHR) at the new secons,

- sa succiliary left term treatment (AUL) at the new access,
- provision of a concrete spitter median in the new access
- concrete island left in, left out only, arrangement at the existing access,
- an anniliary left new treasment with a short turn slot (AUL(S)) at the existing
- a channelised right into treatment with a short turn slot [CHP(S)] into Husper Street
- a concrete pedesirian refuge in Front Sheet north of Hurner Street.

Category V3 lighting is required for this project.

Lighting standards have changed in record times. The lighting installation will need to comply with the following:

- The Ricerical Scriety Art and regulations 2002
  Australian Standards (AS11SE.1.1 2005 Lighting for made and public spaces, AS3000 2000 Australian wiring rules for electrical installations)
- DMR Road Planning & Design Manual (RP&DM) Chapter 17
- MR specifications MRS11.91, MRS11.92, MRS11.94 and MRS11.95
- MR Stendard Drawings
- District specific standards, notes and drawing details (made available on request)

RPEQ (electrical) certification is mandatory.

Any necessary relocation of Council water coins, Telepa and electrical previous are to be endertaken at no cost to DMR and works completed to the service provider's satisfaction. No existing waver resine within 3.0 m. of the new reside shoulder edge shall be permitted.

- (ii) The landowner applicant shall submit design drawings prepared by a suitably qualified Registered Frofessional Engineer Queensland (RFEQ) for approval of the Caims office of the Department of Main Reads prior to commercing works within the Sinte-controlled read reserve (i.e., Front Street).
- (iii) All required mediaccess works aball be completed to the satisfaction of the Director-General of the Department of Main Roads prior to the commencement of the approved use on the subject lead.

#### Hydraniic Considerations

To protect the existing flood insumity of the Sinte-convolled mad (i.e. Front Street), the Lundowner' applicant sind serk the approval of the Director-General of the Department of Main Reads prior to any works converseing on the subject land which may work in changes to the suitting water flows, niflux levels and/ or hydranic structures along, under or over Front Street.

-3-

#### Visual Amenity Treatments 4

The applicant improves a shall provide a minimum 3ra wide lambscaped strip and building alignment serback along the subject hands frontage to Front Street to serson the source carparking provision and vehicular circulation. The landscaping shall be designed and platted much that whose the fund-scaping matures, it provides a minimum 1 as high surraning and complementary screen trees approximately for tall at 7m spacings.

The species of plants used in the landscaping works shall be in necessaries with Council's standards. If Council does not have standards, then the only requirements are that the species are native, few makessance species that are wiffering at providing the promisery screening specified above and do not create a safety risk (i.e. no therms, pursuance of wide us berries or large zots).

All landscaping works shall be completed prior to the communectment of the approved use, to the actifaction of the Director-General of the Department of Main Roads and the Douglas Stine Council.

#### Provision of Palastrian Bicycle Path

- (i) The applicant/landowner shall provide a 2m wide conserving potentian/ bicycle path along the full Front Street frontage, with finks into the proposed development sorth and acuts of the existing road secess location, subject to the approval of the Department of Main Roads.
- (ii) The applicant/landowner shall construct the pedestries/bloydle path to the requirements of the Houghs Shire Council prior to the commencement of the appeared see on the subject land.

#### Parking

When calculating emparising requirements essociated with the proposed development, no allowance shall be made for parking within the State-controlled codd reserves (i.e. Front

#### Advirtidag

No advertising device for the proposed development on the subject land is permitted within the State-controlled road reserves (i.e. Front Street).

#### Resector

The reasons and information used in the netting of conditions detailed above include:

Department of Main Roads Access Follogs

Department of Main Roads Involvement in Development Application Referrate and

- Ameument Guide; and
- Douglas Shire Planning Scheme.

#### B. GINERAL DISCUSSION

Council is requested to reflect the above conditions on its Rates Record, to one or that the planning intentions of the conditions are secured.

This Department would appreciate a copy of Conneil's decision accide regarding the application.

-4-

A copy of this letter has been sent to the applicant.

Yours sincerely

David Hotor Manager (transport Planning) Peninsula

### FNQROC DEVELOPMENT MANUAL

Council CATRNS RECTION AC COUNCIL (INSERT COUNCIL NAME)

### STATEMENT OF COMPLIANCE **OPERATIONAL WORKS DESIGN**

This form duly completed and signed by an authorised agent of the Designer shall be submitted with the Operational Works Application for Council Approval.

Name of Development MOSSMAN CATENAY SHOPPING CENTRE

Compliance with the requirements of the Operational Works Design Guidelines	Non-Compliance refer to non-compliance report / drawing number		
Plan Presentation	SITE PLAN ATTRICHED		
Geotechnical requirements	GROTELHILLAR ROBERT ATTACHED		
Geometric Road Design	NIA		
Pavements	NIA		
Structures / Bridges	NIR		
Subsurface Drainage	NIA		
Stormwater Drainage	STORMWATTER DESIGN PLANS ATTACHED		
Site Re-grading	1/9		
Erosion Control and Stormwater Management	UNDER SERMATE CONER		
Pest Plant Management	NA		
Cycleway / Pathways	NA		
Landscaping	LANDSAANG PREVIOUSLY APPROVED		
Water Source and Disinfection/Treatment Infrastructure (if applicable)	ala		
Water Reticulation and Pump Stations	WATER SUPPLY PLANS ATTACHED		
Sewer Reticulation and Pump Stations	PLUMBING APPROVIAL HAS BRON ISLUED		
Electrical Reticulation and Street Lighting	NA		
Public Transport	NIA		
Associated Documentation/ Specification	N/A.		
Priced Schedule of Quantities	N/R		
Referral Agency Conditions	NIX		
Other FNOROC DEVELOPMENT MANUAL	Аррелдіх А		

FNOROC DEVELOPMENT MANUAL APPLICATION PROCEDURES AP1 - 01/09

APPLICATION PROCEDURES
Location of Development 63 FRONT STREET, MOSSMAN
Applicant TOWN & COUNTRY UTD
Designer TRG
It is hereby certified that the Calculations, Drawings, Specifications and related documents submitted herewith have been prepared, checked and amended in accordance with the requirements of the FNQROC Development Manual and that the competed works comply with the requirements therein, except as noted below.
Conscientiously believing the above statements to be true and correct, signed on behalf of:
Designer RPEQ No
Name in Full
Signature Date

## **OPERATIONAL WORKS RECEIPTING CHECKLIST**

(To be completed by Consulting Engineer making the application)

Name of Council: CAIRNS REGIONAL CO	UNCIL		
Development Name and Location:	CATEWAY	SHOPPIN	C,
CENTRE - 63 FRONT STREET	,	<b>~</b>	
Planning Permit No/Council File No:	812		
DESIGN SUBMISSION	<u>CHECK</u>	COMMENT	
<ol> <li>Completed 'Statement of Compliance' form. (FNQROC - AP1 – Appendix A)</li> </ol>			
<ol><li>IDAS Forms A ,E &amp; IDAS Assessment Checklist (Available from <a href="www.ipa.gld.gov.au">www.ipa.gld.gov.au</a>)</li></ol>	V		
<ol> <li>Payment of Engineering Application Fees (Copy of receipt to be attached) (Available from <a href="https://www.cairns.gld.gov.au">www.cairns.gld.gov.au</a>)</li> </ol>			
<ol> <li>Copy of Decision Notice for Development Application Conditions, inc. explanation of how each condition is to be addressed (Statement of Compilance)</li> </ol>			
<ol> <li>Engineering Design drawings -         Complete sets (1 x A1 set, 2 x A3 sets and         1 x electronic copy on compact disc in 'PDF' format)</li> </ol>	Image: section of the content of the		
<ol><li>One copy of Design and Standard Specifications (Unbound Copy Preferable)</li></ol>			
<ol><li>Written consent from adjoining property owners authorising any works on their property</li></ol>			
Water reticulation network in electronic format     (Engineer to confirm system requirements and compatibility with Calrns Water)	I		
ਬ.)Landscape drawings - Complete set (1 x A1 set, 2 x A3 sets and 1 x electronic copy on compact disc in 'PDF' format) These must be accompanied by elements of the stormwater & street itg. layout design, to avoid conflicts.	PROV.	auszy As	°PROV€0
10. Overall network drawings (for staged development) for:			
Water	<b>I</b>		
Stormwater			
• Sewer			
Pathways and roads			
Street Lighting			

# **OPERATIONAL WORKS RECEIPTING CHECKLIST (Continued)**

<u>DESIGN SUBMISSION</u>		<u>C</u>	HECK	COMMENT
40. Overall network drawing	s (for staged dev	elopment) Cont	inued.	
<ul> <li>Electrical</li> </ul>				
• Gas				
<ul> <li>Public Transport</li> </ul>				
<ul> <li>Park Reserves</li> </ul>				
Drainage Reserves				
11. Pavement design criteria	•			
12. Geotechnical reports for	proposed Earthw	orks		
. 13. Structural and geotechnic retaining walls etc.	cal certificates for	. [		
114. Water supply/sewerage p	oump station des	gn parameters		
15. Stormwater drainage calc	culations			
16. Erosion and Sediment Co	ontrol Strategy (E	scs) [		
, 17. Declared Pest Manageme	ent Plan (if applic	able)		
18. The approval of any other agencies likely to be affect				
19. Contact details of the Con	sulting Engineer	who is submitti	ng the Applica	tion:
Name of Engineer	TO BE	Aovisão		
Name of Company				
Telephone Number (s)	Office:		Mobile:	
Email address				
RPEQ No.				
20. Date of submission of ap	plication .!a/.	4.7 20 <b>0</b> 9		
(For further Information on all of the above refer to the FNQROC Development Manual Section AP1)				
PLEASE RETURN THIS FORM A CUSTOMER SERVICES DESK,				



(Caims) Pty Ltd Unit 1, 220 Scott St Caims Old 4870 Telephone: 07 4047 8600 Facsimile: 07 4047 8699 Nata Accred. No: 1833

PO 8ex 252 Bungalow Old 4870

(Townsville) Pty Ltd Unit D 26-30 Loma Court Bohle Qid 4618 Telephone: 07 4774 4135 Facsimile: 07 4774 4357 Nata Accred. No: 2694

Advice no. TE07-178-003L 15 February 2008

Town and Country PO Box 100 MOSSMAN QLD 4873

Attention: Mr Stuart Lovell

Dear Stuart,

RE: ADVICE REGARDING PROPOSED SHOPPING CENTRE CAPTAIN COOK HIGHWAY, MOSSMAN

#### INTRODUCTION 1.0

Engineering Testing Services (Townsville) Pty Ltd (ETS) has conducted a geotechnical investigation for a proposed shopping centre redevelopment at Mossman. The works were commissioned by Stuart Lovell of Town and Country, November 2007.

The current document presents revised design recommendations for proposed footings at the shopping centre site based on new design information supplied subsequent to the issuing of ETS previous report TE07-178-002R. The additional design drawings for the existing complex were supplied to ETS by DEQ Consulting Engineers (on behalf of Town and Country). Initial design recommendations for footings are presented in TE07-178-002R issued early January 2008.

#### 2.0 **ENGINEERING ASSESSMENT**

Due to the variability in shopping centre layouts, a suspended slab is not a preferred footing option. Proposed footing options were supplied to ETS on 25 January 2008. This document is to supplement the previous report issued and provide design recommendations for a slab-on-ground footing scenario based on the loads supplied by DEQ Consulting Engineers.

The following have been assumed for the assessment of total and differential settlements:



Engineering Testing Services (Cairns) Fty Ltd Unit 1, 220 Scott St Cairns Clid 4870 Telaphone: 07 4047 8699 Nata Accred, No: 1833

PO Box 252 Bungalow Old 4870

Engineering Testing Services (Townsville) Pty Ltd Unit D 28-30 Lorna Court Bothe Old 4818 Telephone: 07 4774 4135 Facsimile: 07 4774 4357 Nata Accred. No: 2694

 The upper 1m (approximately) of soil is to be removed and replaced with controlled fill as per recommendation supplied in Section 3.0 of this document. All subsurface material containing organic materials should be removed prior to fill be placed on site. It is considered unlikely that the current upper 1m of soil in the profile could be reused as controlled fill.

- The ultimate limit state design load for the proposed supermarket is ≤30kPa.
   Additionally the width of the supermarket is approximately 60m.
- The ultimate limit state design load for the proposed retail store is ≤10kPa.
   Additionally the width of the retail store is approximately 30m.
- Fill material is assumed to have a unit weight of approximately 20kN/m³.
- Strip footings are proportioned using an allowable bearing capacity of 100kPa with >0.7m of controlled fill below the base of the footing.
- Pad footings are proportioned using an allowable bearing capacity of 150kPa with >1m of controlled fill below the base of the footing.
- An assessment settlement has been performed using Schmertmann's method in conjunction with generally accepted geotechnical engineering principles.
   Differential settlements are anticipated to be approximately 75% of the total settlements.

Based on the above assumptions total settlements of approximately 30mm are anticipated for the site, corresponding to differential settlements of approximately 20 – 25mm.

#### 3.0 SITE FILLING AND SUBGRADE PREPARATION

Subgrade preparation should consist of complete removal of topsoil (upper layer of soil containing grass roots and organic matter) and fill material, followed by proof rolling and compaction to a minimum dry density ratio of 95% based on Standard compactive effort (for clayey soils). 'Soft', wet areas remaining after subgrade treatment should be excavated, backfilled and compacted with an approved select fill material. Backfill shall be placed and compacted in layers not exceeding 200mm loose thickness to the above density ratio.



Engineering Testing Services Engineering Testing Services (Cairns) Pty Ltd Unit 1, 220 Scott St Caims Old 4870 Telephone: 07 4047 8600 Facsimile: 07 4047 8699 Nata Accred, No: 1833

PO 8ex 252 Bungalow Qld 4870

(Townsville) Pty Ltd Unit 9 26-30 Loma Court Bohle Qld 4818 Telephone: 07 4774 4135 Facsimile: 07 4774 4357 Nate Accred, No: 2694

Where filling it should be placed and compacted in a controlled manner. Controlled filling should be carried out as per the specifications of the works, and in the absence of specifications works should be conducted as per AS3798-2007 ("Guidelines on Earthworks for Commercial and Residential Developments").

If fill material is to be imported it is recommended that the fill should comprise what is locally known as "CBR 15 material" and have a Plasticity Index less than 20. Further geotechnical advice should be sought if reactive fill is used.

In regard to the potential issue of workability of the cut surface of the replacement zone, it is anticipated that some construction difficulties may be possible in the soft to firm sandy clay material, especially if the ground becomes saturated or wet. In the event that the workability of the cut surface is difficult the use of a bridging layer may be adopted, where a layer of geofabric is placed over the base and sides of the fill body and suitable compacted material is placed. ETS would be pleased to provide a detailed design of a suitable bridging layer platform if required. Alternatively, material difficult to handle may be excavated until a suitable founding layer is observed, the excavation may then be replaced with compacted fill.

It is also noted that if the clay soil on site becomes 'wet' it is likely to result in trafficability problems, and placement of material on site would become difficult.

#### 4.0 CONCLUSION

Given the above it is recommended that the ground slab be reassessed from a structural viewpoint to ensure that adequate stiffness is provided to accommodate the assessed settlements discussed in previous sections.

We have prepared this report for the use of Town and Country, for design purposes in accordance with generally accepted geotechnical engineering practices. No other warranty, expressed or implied, is made as to the professional advice included in this report. This report has not been prepared for use by parties other than Town and Country or their design consultants, ie. Architect & Civil/Structural Engineers. It may not contain sufficient information for purposes of other parties or for other uses.

Your attention is drawn to the document - "Important Information About Your Geotechnical Engineering Report", which is attached to this advice. This document has been prepared by the ASFE (Professional Firms Practicing in the Geosciences). The statements presented in this document are intended to advise you of what your realistic expectations of this report should be, and to present you with



Engineering Testing Services (Cairns) Pty Ltd (Townsville) Pty Ltd (Caims) Pty Ltd Unit 1, 220 Scott St Cairns Qld 4870 Telephone: 07 4047 8600 Facsimile: 07 4047 8699 Nata Accred. No: 1833

Unit D 26-30 Loma Court Bohle Qld 4818 Telephone: 07 4774 4135 Facsimile: 07 4774 4357 Nata Accred. No: 2694

PO Box 252 Bungalow Qld 4870

recommendations on how to minimise the risks associated with the groundworks for this project. The document is not intended to reduce the level of responsibility accepted by ETS, but rather to ensure that all parties who may rely on this report are aware of the responsibilities each assumes in so doing.

Should you require clarification on any aspect of this proposal, please do not hesitate to contact Chris Pennisi at our Townsville Office.

Yours faithfully,


**ENGINEERING TESTING SERVICES (Townsville) PTY LTD** 

Michael Ganza (RPEQ 4449)

Director

# Jupportant Information About Your

# Geotechnical Engineering Report



# Geotechnical Services Are Performed for Specific Purposes, Persons, and Projects

Geotechnical engineers structure their services to meet the specific needs of their clients. A geotechnical engineering study conducted for a civil engineer may not fulfil the needs of a construction contractor or even another civil engineer. Because each geotechnical engineering study is unique, each geotechnical engineering report is unique, prepared solely for the client. No one except you should rely on your geotechnical engineering report without first conferring with the geotechnical engineer who prepared it. And no one – not even you – should apply the report for any purpose or project except the one originally contemplated.

# A Geotechnical Engineering Report Is Based on A Unique Set of Project-Specific Factors

Geotechnical engineers consider a number of unique, project-specific factors when establishing the scope of a study. Typical factors include: the client's goals, objectives, and risk management preferences; the general nature of the structure involved, its size, and configuration; the location of the structure on the site; and other planned or existing site improvements, such as access roads, parking lots, and underground utilities. Unless the geotechnical engineer who conducted the study specifically indicates otherwise, da not rely on a geotechnical engineering report that was:

- not prepared for you,
- not prepared for your project,
- not prepared for the specific site explored, or
- completed before important project changes were made.

Typical change that can erode the reliability of an existing geotechnical engineering report include those that affect:

- the function of the proposed structure, as when it's changed from a parking garage to an office building, or from a light industrial plant to a refrigerated warehouse.
- elevation, configuration, location, orientation, or weight of the proposed structure,
- · composition of the design team, or
- project ownership,

As a general rule, always inform your geotechnical engineer of project changes – even minor ones – and request an assessment of their impact. Geotechnical Engineers cannot accept responsibility or liability for problems that occur because their reports do not consider developments of which they were not informed

### Subsurface Conditions Can Change

A geotechnical engineering report is based on conditions that existed at the time the study was performed. Do not rely on a geotechnical engineering report whose adequacy may have been affected by: the passage of time; by man-made events, such as construction on or adjacent to the site; or by natural events, such as floods, earthquakes, or groundwater fluctuations. Always contact the geotechnical engineer before applying the report to determine if it is still reliable. A minor amount of additional testing or analysis could prevent major problems.

# Most Geotechnical Findings Are Professional Oninions

Site exploration identifies subsurface conditions only at those points where subsurface tests are conducted or samples are taken. Geotechnical engineers review field and laboratory data and then apply their professional judgement to render an opinion about subsurface conditions throughout the site. Actual subsurface conditions may differ – sometimes significantly – from those indicated in your report. Retaining the geotechnical engineer who developed your report to provide construction observation is the most effective method of managing the risks associated with unanticipated conditions.

# A Report's Recommendations Are Not Final

Do not overrely on the construction recommendations included in your report. Those recommendations are not final, because geotechnical engineers develop them principally from judgement and opinion. Geotechnical engineers can finalise their recommendations only by observing actual subsurface conditions revealed during construction. The geotechnical engineer who developed your report cannot assume responsibility or liability for

the refort's recommundations if that engineer does not perform construction observation.

# A Geofechnical Engineering Report Is Subject to Misinterpretation

Other design team members' misinterpretation of geotechnical engineering reports has resulted in costly problems. Lower that risk by having your geotechnical engineer confer with appropriate members of the design team after submitting the report. Also retain your geotechnical engineer to review pertinent elements of the design team's plans and specifications. Contractors can also misinterpret a geotechnical engineering report. Reduce that risk by having your geotechnical engineer participate in prebid and preconstruction conferences, and by providing construction observation.

## Do Not Redraw the Engineer's Logs

Geotechnical engineers prepare final boring and testing logs based upon their interpretation of field logs and laboratory data. To prevent errors or emissions, the logs included in a geotechnical engineering report should never be redrawn for inclusion in architectural or other design drawings. Only photographic or electronic reproduction is acceptable, but recognise that separating logs from the report can elevate risk.

# Give Contractors a Complete Report and Guidance

Some owners and design professionals mistakenly believe they can make contractors liable for manticipated subsurface conditions by limiting what they provide for bid preparation. To help prevent costly problems, give contractors the complete geotechnical engineering report, but preface it with a clearly written latter of transmittal. In that letter, advise contractors that the report was not prepared for purposes of bid development and that the report's accuracy is limited; encourage them to confer with the geotechnical engineer who prepared the report (a modest fee may be required) and/or to conduct additional study to obtain the specific types of information they need or prefer. A prebid conference can also be valuable. Be sure contractors have sufficient time to perforn additional study. Only then might you be in a position to

give contractors the best information available to you, while requiring them to at least share some of the financial responsibilities stemming from unanticipated conditions.

#### Read Responsibility Provisions Closely-

Some clients, design professionals, and contractors do not recognise that geotechnical engineering is far less exact than other engineering disciplines. This lack of understanding has created unrealistic expectations that have led to disappointments, claims, and disputes. To help reduce such risks, geotechnical engineers commonly include a variety of explanatory provisions in their reports. Sometimes labelled "limitations", many of these provisions indicate where geotechnical engineers responsibilities begin and end, to help others recognise their own responsibilities and risks. Read these provisions closely. Ask questions. Your geotechnical engineer should respond fully and frankly.

# Geoenvironmental Concerns Are Not Covered

The equipment, techniques, and personnel used to perform a geoenvironmental study differ significantly from those used to perform a geotechnical study. For that reason, a geotechnical engineering report does not usually relate any geoenvironmental findings, conclusions, or recommendations; e.g., about the likelihood of encountering underground storage tanks or regulated contaminants. Unanticipated environmental problems have led to numerous project failures. If you have not yet obtained your own geoenvironmental information, ask your geotechnical consultant for risk management guidance. Do not rely on an environmental report prepared for someone else.

# Rely on Your Geotechnical Engineer for Additional Assistance

Membership in ASFE exposes geolechnical engineers to a wide array of risk management techniques that can be of genuine benefit for everyone involved with a construction project. Confer with your ASFE member geotechnical engineer for more information.



Copyright 1998 by ASFE, Inc. Unless ASFE grants written permission to do so, deplication of this document by any means whatsoever is expressly prohibited. Re-use of the wording in this document, in whole or in part, also is expressly prohibited, and may be done only with the express permission of ASFE or for purposes of review of scholarly research.



# GEOTECHNICAL INVESTIGATION

**PROJECT NO: TE07-178** 

TOWN & COUNTRY SHOPPING CENTRE REDEVELOPMENT MOSSMAN

**JANUARY 2008** 

PO Box 252, Bungalow Qld 4870 Ph: (07) 4774 4135 Fax: (07) 4774 4357 Mob: 0439 773 379 Email: info@engineeringtesting.com.au

# REPORT ON

# **GEOTECHNICAL INVESTIGATION**

# PROPOSED SHOPPING CENTRE REDEVELOPMENT MOSSMAN

Submitted to:

Town & Country PO Box 100 MOSSMAN QLD 4873

# DISTRIBUTION:

2 Copies -Town & Country

1 Copy - Engineering Testing Services (Townsville) Pty Ltd

January, 2008

TE07-178-002R

# **TABLE OF CONTENTS**

SECTION			
1.0	INTRODUC	TION	1
2.0		2	
3.0		PRY TESTING	
4.0		ITIONS AND OBSERVATIONS	
		oil Conditions	
5.0		ING ASSESSMENT	
		ng Design	
		Site Classification	
		Pier Footings	
		Filling and Subgrade Preparation	
6.0		<b>1</b> S	
LIST	OF APPEND	ICES	
Append	dix A	Results of Fieldwork	
Append	dix B	Laboratory Testing - Classification Testing	
Appendix C		"Important Information about your Geotechnical I	Engineering

### 1.0 INTRODUCTION

Engineering Testing Services Pty Ltd (ETS) has conducted a geotechnical investigation for the proposed Town & Country shopping centre redevelopment. The works were commissioned by the customer in October 2007.

It is understood the proposed redevelopment involves an extension to the existing Town & Country shopping centre located on the Captain Cook Highway, Mossman. The redevelopment is to include construction of specialty shops, a new supermarket, offices and associated amenities. It is also understood that additional car parking facilities will be constructed to service the shopping centre patrons.

Based on the plans provided, it is likely that part of the extension will be two storeys. It is noted that design foundation loads for the proposed redevelopment have not been provided.

Based on the above information, the extent of works covered by ETS in this report is as follows:

- Provide a site classification in accordance with AS2870 1996 "Residential Slab and Footing Construction" to allow the selection of standard footing designs or for the design of footing systems by engineering principles.
- Provide an indication of materials which may be encountered on site by supplying detailed engineering logs and confirmatory classification testing to confirm material type observed in the field. Detailed logging of boreholes and test pits will be conducted in accordance with AS1726 "Geotechnical Site Investigations" and under the direction of an experienced Geotechnical Engineer.
- Provide advice on suitable founding options and subsequent allowable bearing capacities for expected founding materials. If piers are considered a feasible option, design parameters will be provided.
- Provide advice on methods of excavation for the material encountered.
- Provide advice on suitable methods for site preparation and earthworks.
- Provide quantitative California Bearing Ratio (CBR) values to facilitate pavement design.

### 2.0 FIELD WORK

Fieldwork was conducted on the 5, 11 and 12 December 2007 and included an assessment of the site and its surrounds, and subsurface investigation of material on site. Fieldwork was conducted by ETS Senior Geotechnician Darren Koch.

Four (4) boreholes were drilled to approximately 10.95m to 13.45m depth across the site to assess subsurface materials. Boreholes were drilled using a trailer mounted drilling rig equipped for geotechnical investigations. Insitu testing and sampling was conducted at approximately 1m to 1.5m intervals using Standard Penetration Testing (SPT) and/or thin wall U50 tubes, where appropriate.

Seven (7) test pits were excavated on site using a backhoe equipped for geotechnical investigations. Test pits were excavated to depths between 4.2m and 4.5m. Disturbed bulk samples were retrieved from test pits to facilitate CBR testing.

The approximate locations of each of the borehole and test pit can be viewed on the attached Figure 1.

Engineering logs for each of the boreholes may be seen in Appendix A.

Samples collected were sealed and transported to ETS NATA accredited Cairns laboratory for further classification and testing.

At the time of the fieldwork, groundwater inflow was observed in BH1 and BH2 at approximately 6.6m and 6.3m respectively, below the ground surface level. It is noted that higher groundwater levels may be possible due to rain, broken services, and/or other factors.

### 3.0 LABORATORY TESTING

The following laboratory testing was conducted in our NATA accredited laboratory on samples recovered during fieldwork:

- 7 Atterberg Limits to aid in site and soil classification.
- 10 Particle Size Distribution to aid in site and soil classification.
- 3 Standard Compaction and 4-Day Soaked CBR tests

The results for the laboratory testing are presented in Appendix B.

Please note that CBR results will included as part of a subsequent report.

#### 4.0 SITE CONDITIONS AND OBSERVATIONS

#### 4.1 Subsoil Conditions

Based on the four (4) boreholes and seven (7) test pits excavated on site, the general subsoil strata is as follows:

TABLE 1: General Subsoil Profile

Depth (m)	MATERIAL Description			
Ground Level (0.0m)	SANDY / SILTY CLAY			
1.5	Soft to firm, orange, brown, pale yellow and pale grey			
1.5m	CLAYEY / SILTY SAND:			
	Loose to medium dense, yellow and brown			
	to			
	SANDY /SILTY CLAY:			
3.5m	Firm to very stiff, yellow and brown.			
	SANDY / SILTY CLAY			
	Firm to very stiff yellow, orange, brown and grey.			
	to			
	SILTY SAND			
0.0	Medium dense, yellow, orange, brown and grey.			
8.0m				
	SILTY / CLAYEY /GRAVELLY SAND			
	Medium dense to dense, pale grey, cream and pale yellow			
13.5m				

The subsoil profile each of the observed in boreholes BH1 to BH4 and TP1 to TP7 can be viewed in the engineering logs in Appendix A.

# 5.0 ENGINEERING ASSESSMENT

# 5.1 Footing Design

Given the very soft to soft clays and loose sands observed to depths of approximately 3.5m below the existing surface, it is considered that a suspended slab with piles is a feasible footing system. It is considered that shallow footings and stiffened rafts will be prone to significant settlements, and hence unlikely to be

feasible from a serviceability and strength viewpoint. ETS would be pleased to provide a more detailed assessed for shallow foundations if requested.

Design recommendations for piles and general earthworks are provided in the sections below. For completeness a site classification as also been provided in Section 5.1.1 below.

#### 5.1.1 Site Classification

A site classification in accordance with AS2870 has been conducted below to aid in the design of the footings.

In assessment of site classification the following have been considered:

- The depth of suction change Hs has been taken as 1.5 metres based on the
  recently published work by Fox (2000) and in accordance with local practice,
  with a design suction change at ground surface of pF 0.8. A crack depth of
  0.8m has been assumed as per AS2870.
- Typical shrink-swell parameters have been assessed by an empirical correlation with classification test (liquid limit and/or linear shrinkage).

Based on the results of the Atterberg Limit and Particle Size Distribution testing the materials encountered on site is assessed to have a characteristic free surface movement of approximately 30 mm.

Due to the very soft to soft soils encountered during the investigation the Site may be classified **CLASS** – **P** for footings designed in accordance with Australian Standard 2870 "Residential Slabs and Footings – Construction" and advice should be sought from a Qualified Engineer (a professional engineer with academic qualifications in geotechnical or structural engineering who also has extensive experience in the design of footing systems for houses or similar structures).

Note: This classification is subject to review should any cut earthworks in excess of 0.5m or any filling be carried out.

## 5.1.2 Pier Footings

Piles may be adopted to support the structures forming this development. A number of pile types could be utilised for the proposed structure depending on constraints such as allowable vibration levels during construction and council approvals. To aid in preliminary design recommendations for bored and driven piles are provided in this report.

It is noted that driven then cast in-situ piles with an enlarged base (such as Frankipiles) generally have similar advantages and disadvantages as driven precast piles, but with the further advantage of higher bearing or tensile capacity due to the enlarged base.

For the current project, bored piles advanced from the base of the proposed excavation are likely to require use of liners to reduce difficulties with groundwater entry into the drilled boreholes.

It is noted that if some seepage may be expected in the bored pier holes. It is suggested that seepage water be pumped from the hole immediately prior to concrete being placed.

An alternative approach to using a liner for bored piles would be to use a CFA pile rig for which the hollow flight auger supports the borehole sides and permits concrete injection to the base of the hole.

For driven piles, the piles would need to be hammered to a sufficient depth to allow adequate skin friction to be achieved for the design against uplift loads due to pore water pressure.

Design parameters for non-displacement (i.e. bored) and displacement (i.e. driven) pile types are shown in Table 2 below. To obtain the assessed design parameters piles should be embedded at least three pile diameters into the soil layer. Greater founding depths may be required for large uplift or compression loads. The design should include assessment of both strength and serviceability limit states. A geotechnical reduction factor of  $\Phi_g=0.5$  should be applied to the ultimate end bearing and shaft resistance values indicated in Table 2 when considering the ultimate strength limit state.

TABLE 2: Preliminary Ultimate Design Capacities for Boreholes BH1 - BH4

Soil Type	Depth (1)	Ultimate Bearing Capacity (MPa)		Ultimate Skin Friction			
				Non-displacement		Displacement	
		Non- displacement	Displacement	Compression (kPa)	Tension (kPa)(2)	Compression (kPa)	Tension (kPa)(2)
Sandy sifty CLAY: Soft to firm	0 1.5m	Neglect	Neglect	Neglect		Neglect	
Clayey / silty SAND to sandy / silty CLAY: Loose to medium dense / firm to very stiff	1.5 – 3.5m	0.5	0.8	15	12	25	20
Sandy / silty CLAY to silty SAND: Firm to very stiff, medium dense	3.5 – 8.0m	0.8	1.0	30	25	40	35
Silty / clayey / gravelly SAND: Medium dense to dense	8.0 – 13.0m	2.0	3.5	35	30	60	45

- 1. Depths are below current ground surface level.
- 2. A factor of 0.8 (\*ultimate skin friction compression) has been used to obtain the ultimate skin friction tension for sandy soils (Decourt, 1995).

The ultimate end bearing pressure and shaft resistance have been estimated based on the empirical method of Decourt (1995). For preliminary design the pile footings may be sized using the ultimate values given in this section. The final proposed pile sizes need to be checked by a Geotechnical Engineer from a serviceability point of view.

The footing excavations should be assessed before placement of concrete by a suitably qualified and experienced geotechnical engineer (or an experienced Geotechnician under direction of a geotechnical engineer), to confirm that founding conditions are consistent with those recommended above.

### 5.2 Site Filling and Subgrade Preparation

Subgrade preparation should consist of complete topsoil removal (upper layer of soil containing grass roots and organic matter), excavation to the depth of the trench, followed by compaction of the base of the trench to a minimum dry density ratio of 95% based on Standard compactive effort (for clayey soils). 'Soft', tree stump holes and/or wet areas remaining after subgrade treatment should be excavated, backfilled and compacted with an approved select fill material. Backfill shall be placed and compacted in layers not exceeding 200 mm loose thickness to the above density ratio.

Where filling it should be placed and compacted in a controlled manner. Controlled filling should be carried out as per the specifications of the works, and in the absence

of specifications works should be conducted as per AS3798-2007 ("Guidelines on Earthworks for Commercial and Residential Developments").

If fill material is to be imported it is recommended that the fill should comprise what is locally known as "CBR 15 material" and have a Plasticity Index less than 20. Further geotechnical advice should be sought if reactive fill is used.

It is also noted that if the clay soil on site becomes 'wet' it is likely to result in trafficability problems, and placement of material on site would become difficult.

### 6.0 LIMITATIONS

We have prepared this report for the use of **Town & Country** for design purposes in accordance with generally accepted geotechnical engineering practices. No other warranty, expressed or implied, is made as to the professional advice included in this report. This report has not been prepared for use by parties other than **Town & Country** or their design consultants, i.e. Architect & Civil/Structural Engineers. It may not contain sufficient information for purposes of other parties or for other uses.

Your attention is drawn to the document - "Important Information About Your Geotechnical Engineering Report", which is included in Appendix C of this report. This document has been prepared by the ASFE (Professional Firms Practicing in the Geosciences). The statements presented in this document are intended to advise you of what your realistic expectations of this report should be, and to present you with recommendations on how to minimise the risks associated with the groundworks for this project. The document is not intended to reduce the level of responsibility accepted by ETS, but rather to ensure that all parties who may rely on this report are aware of the responsibilities each assumes in so doing.

for and on behalf of

ENGINEERING TESTING SERVICES (Townsville) PTY LTD

Yours faithfully,

Chris Pennisi

Geotechnical Engineer

Kate Johnson

Senior Geotechnical Engineer

