GMA Certification Group Pty Ltd BUILDING SURVEYORS





PORT DOUGLAS OFFICE

PHONE:

(07) 4098 5150 (07) 4098 5180


Lot 9 Unit 5 Craiglie Business Park Owen Street CRAIGLIE QLD 4877

POSTAL: P.O. Box 831, PORT DOUGLAS QLD 4877

E-Mail: adminpd@gmacert.com.au Web: www.gmacert.com.au

4 May 2015

The Chief Executive Officer Douglas Shire Council PO Box 723 MOSSMAN Q 4873



Attention:

Development Assessment -- Mr Neil Beck

Dear Sir,

Re: Application for Operational Works

Lot 2 RP742318 Murphy Street, Port Douglas

The Material Change of Use decision notice issued for the above property (MCUC15/2014) was approved with conditions on 15 December 2014. Specifically, conditions 5, 6 & 13 required the submission of an operational works application to Council for external works, geotechnical confirmation and landscaping work to be carried out as part of the development.

We are advised by the applicant that the landscaping works requirement has been satisfied.

Therefore, please find the attached application for Operational Works including external works and geotechnical confirmation regarding the above development. The application includes:

- 1. IDAS Forms 1 & 6;
- 2. 3 x copies of plans; and,
- 3. Geotechnical Report including email confirmation of specific site issues.

Should you require any further information or wish to discuss the application, please contact me on 4098 5150 or by email jevans@gmacert.com.au

Kind Regards,

GMA Certification Group

Encl.

BUILDING APPROVALS & INSPECTIONS

BUILDING CERTIFICATION

FIRE SAFETY AUDITS

IDAS form 1—Application details

(Sustainable Planning Act 2009 version 4.1 effective 4 July 2014)

This form must be used for ALL development applications.

You **MUST** complete **ALL** questions that are stated to be a mandatory requirement unless otherwise identified on this form.

For all development applications, you must:

- complete this form (IDAS form 1—Application details)
- complete any other forms relevant to your application
- provide any mandatory supporting information identified on the forms as being required to accompany your application.

Attach extra pages if there is insufficient space on this form.

All terms used on this form have the meaning given in the *Sustainable Planning Act 2009* (SPA) or the Sustainable Planning Regulation 2009.

This form and any other IDAS form relevant to your application must be used for development applications relating to strategic port land and Brisbane core port land under the *Transport Infrastructure Act 1994* and airport land under the *Airport Assets (Restructuring and Disposal) Act 2008*. Whenever a planning scheme is mentioned, take it to mean land use plan for the strategic port land, Brisbane core port land or airport land.

PLEASE NOTE: This form is not required to accompany requests for compliance assessment.

This form can also be completed online using MyDAS at www.dsdip.qld.gov.au/MyDAS

Mandatory requirements

Applicant details (Note: the applicant is the person responsible for making the application and need not be the owner of the land. The applicant is responsible for ensuring the information provided on all IDAS application forms is correct. Any development permit or preliminary approval that may be issued as a consequence of this application will be issued to the applicant.)

Name/s (individual or company name in full)	am	a vert	1FICA	M617	GRO0 P
For companies, contact name	OPE	27 evan	5		
Postal address	ρ. ο.	Box	831		
	Suburb	PORT	DOJO	was	
	State	Qld		Postcode	4877
	Country	Australia			
Contact phone number	(07) 400	18 5750			
Mobile number (non-mandatory requirement)				=	
Fax number (non-mandatory requirement)					



Email address (non-mandatory requirement)		darryl						
		@ dpa-architects.com						
	olicant's reference number (non-mandatory uirement)							
1.	What is the nature of the development p	roposed and what type of approval is being sought?						
Tal	Table A—Aspect 1 of the application (If there are additional aspects to the application please list in Table B—Aspect 2.)							
a)	What is the nature of the development? (Plea	ase only tick one box.)						
	Material change of use Reconfigu	uring a lot Building work						
b)	What is the approval type? (Please only tick	one box.)						
	<u> </u>	ry approval X Development permit 41 and s242						
c)		cluding use definition and number of buildings or structures where efined as a multi-unit dwelling, 30 lot residential subdivision etc.)						
	CIVIL WORKS							
d)	What is the level of assessment? (Please only	/ tick one box.)						
	Impact assessment X Code asses	ssment						
	ole B—Aspect 2 of the application (If there are litional aspects of the application.)	additional aspects to the application please list in Table C—						
a)	What is the nature of development? (Please	only tick one box.)						
	Material change of use Reconfigu	rring a lot						
b)	What is the approval type? (Please only tick	one box.)						
		y approval Development 41 and s242 permit						
(c)		cluding use definition and number of buildings or structures where efined as a <i>multi-unit dwelling</i> , 30 lot residential subdivision etc.)						
d)	What is the level of assessment?							
	☐ Impact assessment ☐ Code asse	essment						
	le C—Additional aspects of the application (If arate table on an extra page and attach to this	there are additional aspects to the application please list in a form.)						
	Refer attached schedule Not requir							

2.	2. Location of the premises (Complete Table D and/or Table E as applicable. Identify each lot in a separate row.)										
Table D—Street address and lot on plan for the premises or street address and lot on plan for the land adjoining or adjacent to the premises (Note: this table is to be used for applications involving taking or interfering with water). (Attach a separate schedule if there is insufficient space in this table.)											
Street address and lot on plan (All lots must be listed.)											
Street address and lot on plan for the land adjoining or adjacent to the premises (Appropriate for development in water but adjoining or adjacent to land, e.g. jetty, pontoon. All lots must be listed.)											
Street	Street address Lot on plan description Local government area (e.g. Logan, Cairns)										
Lot											
i)		1		urphy Street, l ouglas	Port	4877	2	RF	74:	2318 Po	ort Douglas
ii)											
iii)											
				the premises le. Non-mand		s multiple zo	ones, clear	ly ide	ntify	the relevar	nt zone/s for each lot in a
Lot	Applic	able zone / ¡	orecin	ct	Applica	able local pla	ın / precinct			Applicable	overlay/s
i)											
ii)											
iii)											
adjoin		djacent to l									lot or in water not lule if there is insufficient
	linates place e	each set of	coord	linates in a se	parate r	ow)	Zone refere	nce	Dat	um	Local government area (if applicable)
Eastin	g	Northing		Latitude	Lo	ngitude		ĺ			
										GDA94	
										WGS84	
										other	
3. Tot	3. Total area of the premises on which the development is proposed (indicate square metres)										
638	638										
4. Cur	rent us	e/s of the	ргет	ises (e.g. vac	ant land	d, house, ap	partment b	uilding	g, ca	ane farm etc	c.)
Vacan	Vacant land										

an experience for the following to the content of the content of the content of the first of the content of the

2.

5. Are there any current approvals (e.g. a mandatory requirement)	preliminary approval) associated	with this application? (Non-			
No Yes—provide details below	·	<u> </u>			
List of approval reference/s	Date approved (dd/mm/yy)	Date approval lapses (dd/mm/yy)			
MCUC 15/2014	16 DECEMBER 2014				
6. Is owner's consent required for this app	plication? (Refer to notes at the end	d of this form for more information.)			
X No		<u> </u>			
Yes—complete either Table F, Table G or T	Table H as applicable				
Table F					
	LY ANNE RUNCH	naol			
I/We, the above-mentioned owner/s of the land, of					
Signature of owner/s of the land					
l l	MAN .				
Date 1-5-15					
Table G					
Name of owner/s of the land					
☐ The owner's written consent is attached or w	ill be provided separately to the ass	essment manager.			
Table H					
Name of owner/s of the land					
By making this application, I, the applicant, declar	re that the owner has given written cons	sent to the making of the application.			
7. Identify if any of the following apply to t	he premises (Tick applicable box/e	s.)			
Adjacent to a water body, watercourse or a	quifer (e.g. creek, river, lake, canal)	—complete Table I			
On strategic port land under the <i>Transport</i>	Infrastructure Act 1994—complete T	able J			
In a tidal water area—complete Table K					
On Brisbane core port land under the Trans	sport Infrastructure Act 1994 (No tab	le requires completion.)			
On airport land under the Airport Assets (R	estructuring and Disposal) Act 2008	(no table requires completion)			
Listed on either the Contaminated Land Register (CLR) or the Environmental Management Register (EMR) under the Environmental Protection Act 1994 (no table requires completion)					
Table I					
Name of water body, watercourse or aquifer					
Table J					

Lot on plan description for strategic port land		Port authority for the lot						
Table K								
Name of local government for the tidal area (if applicable) Port authority for the tidal area (if applicable)								
Tamo of local government are and area (it applicable)								
Are there any existing easements or water etc)								
X No Yes—ensure the type, locat	ion and dimension o	of each ease	ement is included in the plans submitted					
Does the proposal include new build services)	ding work or opera	itional wor	k on the premises? (Including any					
☐ No X Yes—ensure the nature, lo	cation and dimension	on of propos	sed works are included in plans submitted					
10. Is the payment of a portable long se end of this form for more information.)	rvice leave levy ap	pplicable to	this application? (Refer to notes at the					
No—go to question 12 X Yes								
11. Has the portable long service leave information.)	levy been paid? (F	Refer to note	es at the end of this form for more					
No Yes—complete Table L and submit with receipted QLeave form	ı this application the	yellow loca	al government/private certifier's copy of the					
Table L								
Amount paid		ate paid d/mm/yy)	QLeave project number (6 digit number starting with A, B, E, L or P)					
	12. Has the local government agreed to apply a superseded planning scheme to this application under section 96 of the Sustainable Planning Act 2009?							
X No								
Yes—please provide details below								
Name of local government	Date of written no by local governme (dd/mm/yy)		Reference number of written notice given by local government (if applicable)					

WAR BURBURD AND DEPART OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE FOREST AND THE FAMILY OF THE PROPERTY OF THE PRO

13. List below all of the forms and supporting information that accompany this application (Include all IDAS forms, checklists, mandatory supporting information etc. that will be submitted as part of this application. Note: this question does not apply for applications made online using MyDAS)

Description of	attachment or title of attachment	Method of lodgement to assessment manager
IDAS Form 1		
IDAS Form 6		
CIVIL	PLANS	
	·	•
1 /		

14. Applicant's declaration

X By making this application, I declare that all information in this application is true and correct (Note: it is unlawful to provide false or misleading information)

Notes for completing this form

Section 261 of the Sustainable Planning Act 2009 prescribes when an application is a properly-made application.
 Note, the assessment manager has discretion to accept an application as properly made despite any non-compliance with the requirement to provide mandatory supporting information under section 260(1)(c) of the Sustainable Planning Act 2009

Applicant details

Where the applicant is not a natural person, ensure the applicant entity is a real legal entity.

Question 1

Schedule 3 of the Sustainable Planning Regulation 2009 identifies assessable development and the type of
assessment. Where schedule 3 identifies assessable development as "various aspects of development" the
applicant must identify each aspect of the development on Tables A, B and C respectively and as required.

Question 6

Section 263 of the Sustainable Planning Act 2009 sets out when the consent of the owner of the land is required for an application. Section 260(1)(e) of the Sustainable Planning Act 2009 provides that if the owner's consent is required under section 263, then an application must contain, or be accompanied by, the written consent of the owner, or include a declaration by the applicant that the owner has given written consent to the making of the application. If a development application relates to a state resource, the application is not required to be supported by evidence of an allocation or entitlement to a state resource. However, where the state is the owner of the subject land, the written consent of the state, as landowner, may be required. Allocation or entitlement to the state resource is a separate process and will need to be obtained before development commences.

Question 7

 If the premises is listed on either the Contaminated Land Register (CLR) or the Environmental Management Register (EMR) under the Environmental Protection Act 1994 it may be necessary to seek compliance assessment. Schedule 18 of the Sustainable Planning Regulation 2009 identifies where compliance assessment is required.

Question 11

• The Building and Construction Industry (Portable Long Service Leave) Act 1991 prescribes when the portable long service leave levy is payable.

ELENGRADO CONTRAR O CONTRAR ESTA MARTINOS PER LAS VEIXA DESCRETA COMO ROS POR LA CERCE ELEMENTA A CERCATA PARA

• The portable long service leave levy amount and other prescribed percentages and rates for calculating the levy are prescribed in the Building and Construction Industry (Portable Long Service Leave) Regulation 2002.

Question 12

The portable long service leave levy need not be paid when the application is made, but the Building and
Construction Industry (Portable Long Service Leave) Act 1991 requires the levy to be paid before a development
permit is issued.

See tenant for the of the tile to ence into the organization of the measure of the ewifall and a second of the execution of t

 Building and construction industry notification and payment forms are available from any Queensland post office or agency, on request from QLeave, or can be completed on the QLeave website at www.qleave.qld.gov.au. For further information contact QLeave on 1800 803 481 or visit www.qleave.qld.gov.au.

Privacy—The information collected in this form will be used by the Department of State Development, Infrastructure and Planning (DSDIP), assessment manager, referral agency and/or building certifier in accordance with the processing and assessment of your application. Your personal details should not be disclosed for a purpose outside of the IDAS process or the provisions about public access to planning and development information in the *Sustainable Planning Act 2009*, except where required by legislation (including the *Right to Information Act 2009*) or as required by Parliament. This information may be stored in relevant databases. The information collected will be retained as required by the *Public Records Act 2002*.

OFFICE USE ONLY			_	_		
Date received			Reference nu	umbers		
OTIFICATION OF EN	GAGE	MENT OF A PRIVA	TE CERTIFIER			
Го					ged as the private this application	certifier for the
Date of engagement	Name	•		BSA Certific number	cation license	Building classification/s
LEAVE NOTIFICATION	ON AND	PAYMENT (For c	ompletion by as	sessment m	anager or private	certifier if
Description of the work	<	QLeave project number	Amount paid (\$)	Date pai	Date receipted form sighted by assessment manager	

The Sustainable Planning Act 2009 is administered by the Department of State Development, Infrastructure and Planning. This form and all other required application materials should be sent to your assessment manager and any referral agency.

IDAS form 6—Building or operational work assessable against a planning scheme

(Sustainable Planning Act 2009 version 3.0 effective 1 July 2013)

This form must be used for development applications for building work or operational work assessable against a planning scheme.

You **MUST** complete **ALL** questions that are stated to be a mandatory requirement unless otherwise identified on this form.

For all development applications, you must:

- complete IDAS form 1—Application details
- · complete any other forms relevant to your application
- provide any mandatory supporting information identified on the forms as being required to accompany your application.

Attach extra pages if there is insufficient space on this form.

All terms used on this form have the meaning given in the *Sustainable Planning Act 2009* (SPA) or the Sustainable Planning Regulation 2009.

This form must be used for building work or operational work relating on strategic port land and Brisbane core port land under the *Transport Infrastructure Act 1994* and airport land under the *Airport Assets (Restructuring and Disposal) Act 2008* that requires assessment against the land use plan for that land. Whenever a planning scheme is mentioned, take it to mean land use plan for the strategic port land, Brisbane core port land or airport land.

This form can also be completed online using MyDAS at www.dsdip.qld.gov.au/MyDAS Mandatory requirements 1. What is the nature of the work that requires assessment against a planning scheme? (Tick all applicable boxes.)												
						Building work—complete Tabl	Building work—complete Table A Operational work—complete Table B					
						a) What is the nature of the building work (e.g. building, repairing, altering, underpinning, moving or demolishing a building)?						
b) Are there any current approvals associated with this application? (e.g. material change of use.) No Yes— provide details below												
List of approval reference/s	Date approved (dd/mm/yy)	Date approval lapses (dd/mm/yy)										



Table B								
a) What is the nature of the operational work? (Tick all applicable boxes.)								
Road works Stormwater Water infras	tructure							
Drainage works Earthworks Dewerage in	frastructure							
☐ Landscaping ☐ Signage ☐ Clearing veg	etation under the pla	anning scheme						
Other—provide details								
h) is the operational work necessary to facilitate the creation of new lote? (F	a subdivision \							
No Yes—specify the number of lots being created	b) Is the operational work necessary to facilitate the creation of new lots? (E.g. subdivision.) No Yes—specify the number of lots being created							
c) Are there any current approvals associated with this application? (E.g. ma	aterial change of use	.)						
List of approval reference/s Date approved (dd/mm/yy)	Date approval lag	oses (dd/mm/yy)						
MCUL 15/2014 16 DEZEMBOR 2014	- 16 DELEMB	2018						
A STATE OF THE STA								
2. What is the dollar value of the proposed building work? (Inc GST, materials and labour.)								
(IIIC 951, Iliateriais and labour.)								
3. What is the dollar value of the proposed operational work? (Inc GST, materials and labour.)	\$	38,000·						
3. What is the dollar value of the proposed operational work?	\$?8,000·						
3. What is the dollar value of the proposed operational work? (Inc GST, materials and labour.)								
3. What is the dollar value of the proposed operational work? (Inc GST, materials and labour.) Mandatory supporting information								
3. What is the dollar value of the proposed operational work? (Inc GST, materials and labour.) Mandatory supporting information 4. Confirm that the following mandatory supporting information according to the proposed operational work? (Inc GST, materials and labour.)	npanies this applic	ation Method of						
3. What is the dollar value of the proposed operational work? (Inc GST, materials and labour.) Mandatory supporting information 4. Confirm that the following mandatory supporting information according to the proposed operation and the	npanies this applic	ation Method of						
3. What is the dollar value of the proposed operational work? (Inc GST, materials and labour.) Mandatory supporting information 4. Confirm that the following mandatory supporting information according to the mandatory supporting information All applications involving building work or operational work A site plan drawn to an appropriate scale (1:100, 1:200 or 1:500 are	npanies this applic Confirmation of lodgement	ation Method of						
 3. What is the dollar value of the proposed operational work? (Inc GST, materials and labour.) Mandatory supporting information 4. Confirm that the following mandatory supporting information according mandatory supporting information All applications involving building work or operational work A site plan drawn to an appropriate scale (1:100, 1:200 or 1:500 are recommended scales) which shows the following: the location and site area of the land to which the application relates 	npanies this applic Confirmation of lodgement	ation Method of						
3. What is the dollar value of the proposed operational work? (Inc GST, materials and labour.) Mandatory supporting information 4. Confirm that the following mandatory supporting information according mandatory supporting information All applications involving building work or operational work A site plan drawn to an appropriate scale (1:100, 1:200 or 1:500 are recommended scales) which shows the following: • the location and site area of the land to which the application relates (relevant land) • the north point • the boundaries of the relevant land	npanies this applic Confirmation of lodgement	ation Method of						
3. What is the dollar value of the proposed operational work? (Inc GST, materials and labour.) Mandatory supporting information 4. Confirm that the following mandatory supporting information according mandatory supporting information All applications involving building work or operational work A site plan drawn to an appropriate scale (1:100, 1:200 or 1:500 are recommended scales) which shows the following: • the location and site area of the land to which the application relates (relevant land) • the north point • the boundaries of the relevant land • the allotment layout showing existing lots, any proposed lots (including the dimensions of those lots), existing or proposed road reserves, building envelopes and existing or proposed open space (note: numbering is required for all lots)	npanies this applic Confirmation of lodgement	ation Method of						
3. What is the dollar value of the proposed operational work? (Inc GST, materials and labour.) Mandatory supporting information 4. Confirm that the following mandatory supporting information according mandatory supporting information All applications involving building work or operational work A site plan drawn to an appropriate scale (1:100, 1:200 or 1:500 are recommended scales) which shows the following: • the location and site area of the land to which the application relates (relevant land) • the north point • the boundaries of the relevant land • the allotment layout showing existing lots, any proposed lots (including the dimensions of those lots), existing or proposed road reserves, building envelopes and existing or proposed open space (note: numbering is	npanies this applic Confirmation of lodgement	ation Method of						
 3. What is the dollar value of the proposed operational work? (Inc GST, materials and labour.) Mandatory supporting information 4. Confirm that the following mandatory supporting information according mandatory supporting information All applications involving building work or operational work A site plan drawn to an appropriate scale (1:100, 1:200 or 1:500 are recommended scales) which shows the following: the location and site area of the land to which the application relates (relevant land) the north point the boundaries of the relevant land the allotment layout showing existing lots, any proposed lots (including the dimensions of those lots), existing or proposed road reserves, building envelopes and existing or proposed open space (note: numbering is required for all lots) any existing or proposed easements on the relevant land and their 	npanies this applic Confirmation of lodgement	ation Method of						

POT HEADERS DESIGNATED AND RESIDENCES DE L'ARREST DE L

A statement about how the proposed development addresses the local government's planning schemes and any other planning documents relevant to the application.	Confirmed	
A statement addressing the relevant part(s) of the State Development Assessment Provisions (SDAP).	Confirmed Not applicable	
Applications for building work (including extensions and demolition that i	is assessable devel	opment)
Floor plans drawn to an appropriate scale (1:50, 1:100 or 1:200 are recommended scales) which show the following:	Confirmed Not applicable	
 the north point the intended use of each area on the floor plan (for commercial, industrial or mixed use developments only) the room layout (for residential development only) with all rooms clearly 		
 tabelled the existing and the proposed built form (for extensions only) the gross floor area of each proposed floor area. 		
Elevations drawn to an appropriate scale (1:100, 1:200 or 1:500 are recommended scales) which show plans of all building elevations and facades, clearly labelled to identify orientation (e.g. north elevation).	Confirmed Not applicable	
Plans showing the size, location, proposed site cover, proposed maximum number of storeys, and proposed maximum height above natural ground level of the proposed new building work.	Confirmed Not applicable	
Plans showing the extent of any demolition that is assessable development.	Confirmed Not applicable	
Applications for operational work involving earthworks (filling and excava	nting)	
Drawings showing:	☑ Confirmed	
existing and proposed contours	Not applicable	
areas to be cut and filled		
 the location and level of any permanent survey marks or reference stations used as datum for the works 		
 the location of any proposed retaining walls on the relevant land and their height 		
the defined flood level (if applicable)		
• the fill level (if applicable).		
Applications for operational work involving roadworks		
Drawings showing:	Confirmed	
existing and proposed contours	Not applicable	
 the centreline or construction line showing chainages, bearings, offsets if the construction line is not the centreline of the road and all intersection points 		
 information for each curve including tangent point chainages and offsets, curve radii, arc length, tangent length, superelevation (if applicable) and curve widening (if applicable) 		
 kerb lines including kerb radii (where not parallel to centreline) and tangent point changes (where not parallel to centreline) 		
edge of pavement where kerb is not constructed		
position and extent of channelisation		
 location and details of all traffic signs, guideposts, guardrail and other street furniture 		
pavement markings including details on raised pavement markers		

Respectively. The provided a second state of the provide action of the second second second and the second second

,			
•	catchpit, manhole and pipeline locations		
•	drainage details (if applicable)		
•	cross road drainage culverts (if applicable)		
•	concrete footpaths and cycle paths		
•	location and details for access points, ramps and invert crossings		
<u> </u>	changes in surfacing material.		<u></u>
A	pplications for operational work involving stormwater drainage		T
Di	rawings showing:	Confirmed	
•	existing and proposed contours	Not applicable	
•	drainage locations, diameters and class of pipe, open drains and easements		
•	manhole location, chainage and offset or coordinates and inlet and outlet invert levels		
•	inlet pit locations, chainage and offset or coordinates and invert and kerb levels.		
A	oplications for operational work involving water reticulation		
Ðr	awings showing:	Confirmed	
	kerb lines or edge of pavement where kerb is not constructed	Not applicable	
•	location and levels of other utility services where affected by water reticulation works		
•	pipe diameter, type of pipe and pipe alignment		
•	water main alignments		
•	water supply pump station details (if applicable)		
•	minor reservoir details (if applicable)		
•	conduits		
•	location of valves and fire hydrants		
•	location of house connections (if applicable)		
•	location of bench marks and reference pegs.		
Αį	oplications for operational work involving sewerage reticulation		
Dr	awings showing:	Confirmed	
•	location of all existing and proposed services	☐ Not applicable	
•	location of all existing and proposed sewer lines and manhole locations		
•	location of all house connection branches		
•	kerb lines or edge of pavement where kerb is not constructed		
•	chainages		
•	design sewer invert levels		
•	design top of manhole levels		
•	type of manhole and manhole cover		
•	pipe diameter, type of pipe and pipe alignment		
•	location of house connections (if applicable) sewer pump station details (if applicable).		
			
	pplications for operational work involving street lighting		
Dr	awings showing:	Confirmed	
•	location of all light poles and service conduits	Not applicable	
•	location of all other cross road conduits		
•	type of wattage and lighting		
•	any traffic calming devices additional plans for roundabouts and major roads (if applicable)		
•	details of any variations to normal alignment		
	· - · · · · · · · · · · · · · · · · · ·		

to the end of the end

diagnacy (12 and 13 and 15 and

details of light	ing levels.					
Applications for	operational work involving pub	lic utility services				
any existing udetails of prop	ght poles and power poles nderground services osed services		Confirmed Not applicable			
	xisting services. operational work involving land	loooning works	<u> </u>	<u> </u>		
Drawings showing the location of a plant schedul numbers of planting bed purpoperation, must be designed by the location are construction designed.	g: i proposed plant species ule indicating common and botanic ants reparation details including topsoil aulch type and depth, type of turf, p and type of any existing trees to be a etails of planter boxes, retaining w maintenance period	cal names, pot sizes and depth, subgrade pebble, paving and garden	Confirmed Not applicable			
Privacy—Please refer to your assessment manager, referral agency and/or building certifier for further details on the use of information recorded in this form.						
OFFICE USE ONL	Υ	ı r		-		
Date received		Reference numbers				

THIS SECTION OF THE HOUSE SECTION OF SECTION OF SECTION SECTIONS FOR THE SECTION OF SECT

The Sustainable Planning Act 2009 is administered by the Department of State Development, Infrastructure and Planning. This form and all other required application materials should be sent to your assessment manager and any referral agency.

Jeff Evans

From:

CACE - Joy Domondon <cace@colefax.net>

Sent:

Monday, 4 May 2015 2:53 PM

To:

Jeff Evans

Subject:

Fw: Doc 435953 130066 Runcimen - 1 Murphy Street, Port Douglas

Hi Jeff,

As per conversation with Bob earlier, see email's below regarding 1 Murphy Street, Port Douglas.

Regards,

Joy

From: Jenny Elphinstone

Sent: Friday, December 12, 2014 9:06 AM

To: 'CACE - Joy Domondon'

Cc: 'Darryl'

Subject: RE: Doc 435953 130066 Runcimen - 1 Murphy Street, Port Douglas

Thanks Joy.

Jenny Elphinstone | Senior Planning Officer

Development & Environment | Douglas Shire Council

P: 07 4099 9482 | F: 07 4098 2902

E: jenny.elphinstone@douglas.qld.gov.au | W: douglas.qld.gov.au

Mail: PO Box 723, Mossman Q 4873 | Office: 64-66 Front St, Mossman Q 4873

From: CACE - Joy Domondon [mailto:cace@colefax.net]

Sent: Wednesday, 10 December 2014 7:25 AM

To: Jenny Elphinstone

Subject: Doc 435953 130066 Runcimen - 1 Murphy Street, Port Douglas

Hi Jenny,

See email below from Golder Associates.

Kind Regards,

Joy

From: Ortega, Ignacio

Sent: Tuesday, December 09, 2014 5:27 PM

To: CACE - Admin 2

Subject: RE: Runcimen - 1 Murphy Street, Port Douglas

Hi Bob and Ash

With regards to your email below, we provide the following comments:

According to the information provided by you, the proposed building will incorporate a suspended floor slab
and will be supported by bored piers and strip footings founded within the recommended founding soils (as
per Section 4.6 of Golder report 04672000-1(B)).

- The proposal to adopt piered structures supported below the fill inferred to be present in the western part of the site addresses issues associated with footing performance. Localised slope failures may still be occur, however landscape planting to Douglas Shire Council requirements will reduce the potential for this.
- Our report 04672000-1(B) dated January 2004 does not strictly follow the risk assessment approach
 indicated in AGS 2007. However, the report provides engineering recommendations to achieve an
 "equivalent" very low to low risk to property in terms of stability issues.

Do not hesitate to contact me should you want to discuss on the above.

Kind regards Ignacio

Ignacio Ortega (MEng (Civil Engineering), MIEAust, CEng-MSpICE) | Senior Geotechnical Engineer | Golder Associates Pty Ltd

216 Draper Street, Cairns, Queensland 4870, Australia (PO Box 5823, Cairns QLD 4870) T: +61 7 4054 8200 | F: +61 7 4054 8201 | E: <u>IOrtega@golder.com.au</u> | <u>www.golder.com</u>

Winner of 22 BRW Client Choice Awards

Work Safe, Home Safe

This small transmission is confidenced and may contain proorietary information for the exclusive use of the intended recipient. Any use, distribution or copying of this transmission, other than by the intended recipient, is strictly prohibited. If you are not the intended recipient, please notify the sender end delete all copies. Electronic media is susceptible to unauthorized modification, deterioration, and incompetibility. Accordingly, the electronic media version of any work product may not be relied upon. Any advice provided in or attached to this email is subject to <u>limitations</u>.

Golder, Golder Associates and the GA globe design are trademarks of Golder Associates Corporation.

Please consider the environment before printing this small.

From: CACE - Admin 2 [mailto:cace@colefax.net]
Sent: Tuesday, 2 December 2014 1:53 PM

To: Ortega, Ignacio

Subject: Runcimen - 1 Murphy Street, Port Douglas

Hi Ignacio,

Further to your discussions with our office I summarise below my understanding of your comments, and my responses in blue to the issues raised:

- The Golders report 04672000-1(B) of 2004 is compliant with AGS 2007
- If the design follows the guidelines in the Golders report of 2004 then it would be considered as 'low risk' in terms of slope stability issues
- The guideline in the 2004 report of removing and replacing existing fill has not been addressed in
 the current design The current design will not be putting any support onto any fill all structure
 over the fill is to be suspended with support founded through the fill into sound residual material
 to a depth that will adequately accept the load without loading the batter.
- The existing batter is not stable in the long term It is our belief that the batter will be stabilised by the piered structures tied back into the main structure footings on the building platform cut into natural residual foundations.
- If the existing fill is to be left as is, the batter should be retained No fill batters will be disturbed
 apart from landscape planting which will be designed to further stabilise the batters (design to be
 by John Sullivan of 'Hortulus' landscape design to Douglas Shire Council requirements).

Also find attached our proposed footing design and building platform preparation specification.

Given the above comments and our attached design will your office provide us with a fee to review our documentation and advise on any revisions required to enable you to issue a cover letter to your 2004 report for Douglas Shire Council stating that the report as is compliant with AGS 2007.

Let me know if you need anything further from our office or if you feel my understanding of your comments is in any way inadequate.

Regards Bob

Colefax Associates Consulting Engineers Pty Ltd 124 Spence Street Cairns PO Box 1769 Cairns QLD 4870 Tel +61 7 4051 9466 Fax +61 7 4051 9477

cace@colefax.net

This document and any attachments are intended solely for the named addressee and are confidential. The copying or distribution of them or any information they contain, by anyone other than the addressee is prohibited. If you have received this document in error, please let us know by telephone and delete all copies from your computer system. It is the user's responsibility to check any attachments to this email for viruses before use

========

This message and any attachments may contain privileged and confidential information intended solely for the use of the intended addressee(s). Any unauthorized use of this material is prohibited. If you received this message in error please notify the sender immediately, delete the message and destroy any printed or electronic copies. Opinions expressed in this email are those of the sender and do not necessarily represent the views of the Douglas Shire Council. We recommend that you scan this email and any attachments for viruses before opening. Council does not accept any responsibility or liability for any loss or damage, incurred either directly or indirectly, from opening this email or any attachments to it, or that may result from reliance on, or the use of, any information contained in this email or attachments. Emails may be monitored and you are taken to consent to this monitoring.

Golder Associates Pty Ltd A.C.N. 006 107 857 A.B.N. 64 006 107 857

216 Draper Street, Calms, Qid 4870 Australia [PO Box 5823, Calms, Qid 4870 Australia] Telephone (07) 4051 2033 Fax (07) 4052 1546 http://www.golder.com



REPORT ON

PROPOSED DEVELOPMENT LOT 2 MURPHY STREET PORT DOUGLAS, QUEENSLAND

Submitted to:

Stephen Ariss
8 Latitude
Murphy Street
Port Douglas QLD 4871

DISTRIBUTION:

2 Copies - Stephen Ariss

l Copy - Golder Associates Pty Ltd

January, 2004

04672000-1(B)








TABLE OF CONTENTS

SECT	ION		PAGE
1.0	INTR	RODUCTION	
2.0	MET	HOD OF INVESTIGATION	.,,,,,,1
	2.1	Fieldwork	
	2.2	Laboratory Testing	2
3.0	RES ¹	ULTS OF INVESTIGATION	2
	3.1	Surface Conditions	2
	3.2	Subsurface Conditions	3
4.0	ENG	INEERING COMMENTS	
	4.1	General	
	4.2	Stability	3
	4.3	Drainage	4
	4.4	Cut and Fill Earthworks	
	4.5	Retaining Structures	
	4.6	Footings	
5.0	IMPO	ORTANT INFORMATION	6

LIST OF FIGURES

Figure I

Site Plan

LIST OF APPENDICES

Appendix A Results of Fieldwork

Appendix B Results of Laboratory Testing

Appendix C "Important Information About Your Geotechnical Engineering Report"

1.0 INTRODUCTION

Golder Associates has carried out a geotechnical investigation on Lot 2, RP 742318, Murphy Street, Port Douglas. The investigation was carried out at the request of Mr Stephen Ariss and was authorised via facsimile on 15 January 2004.

The aims of the investigation were as follows:

- · to evaluate subsurface conditions at the site;
- to comment on the stability of the slopes following proposed development;
- to comment on site preparation and earthworks procedures;
- to comment on the requirement for slope stabilisation/retention and to provide comments on stabilisation/retention options; and
- · to comment on footing options and to provide geotechnical design parameters.

This report presents the results of the investigation together with the engineering comments outlined above.

2.0 METHOD OF INVESTIGATION

2.1 Fieldwork

Fieldwork was carried out on 21 January 2004 and comprised a walk over survey of the site, the drilling of two auger holes (HA1 and HA2) and mapping of the existing cutting at two locations (EX1 and EX2).

An engineering geologist from Golder Associates positioned the test holes, logged the materials encountered, recovered samples and carried out field tests. The approximate locations of the field tests are shown in Figure 1. The results of fieldwork are presented in Appendix A.

2.2 Laboratory Testing

Laboratory testing was carried out on one sample of the materials encountered in the test holes and comprised grading and plasticity tests to confirm field classifications. The laboratory test results are presented in Appendix B and are summarised as follows:

Test Pit No.	HA1
Sample Depth (m)	0.1 - 0.5
Moisture Content (%)	14.8
Liquid Limit (%)	30
Plastic Limit (%)	17
Plasticity Index	13
Percentage Fines (%<75µm)	51
Sample Description	Silty Sandy CLAY

3.0 RESULTS OF INVESTIGATION

3.1 Surface Conditions

The site is located on the western side of Murphy Street and occupies a square shaped area measuring about 25 m by 25 m on a hillside allotment (refer attached Site Plan). It is understood that the existing house at the site was constructed in about 1971. There are existing residences to the north, west and south of the site.

Generally, the site slopes down from Murphy Street to the crest of a cut batter, which then slopes down to the west to the existing building platform. The cut batter has an intermediate berm / walkway and varies in height from about 1 m at the northern end of the site, to about 4 m at the southern end of the site. The cut batter slopes vary from about 30° (northern end) to about 45° (southern end).

The batter below the existing building slopes down to the north-west and west from the existing building platform at 45° to 60° and ranges in height from about 5 m to 7 m.

An access driveway starts from Murphy Street and runs diagonally across the slope towards the existing building platform. Below the driveway and part of the building platform to the north there is a concrete wall up to 4 m high located within the adjacent property.

Other observations in relation to the existing residence and the overall stability of the site are summarised as follows:

- Minor cracking was observed at the base of the brickwork on the western side of the existing residence.
- Minor undercutting and erosion was observed in the steeper areas upslope of the existing residence, with one minor slip observed in the cut batter to the north-east of the residence.

- Boulders were observed on/in the cut batter to the east of the residence.
- A sleeper garden wall is located upslope and to the east of the existing residence.
- The slope below the building platform is very steep and heavily overgrown. It is possible
 that parts of the slope are covered by fill materials.
- The concrete wall to the north-west of the site is intact, and exhibits no visible signs of
 deterioration. It is not known whether subsurface drainage was installed behind the wall
 during construction.

Apart from the building platform and access driveway areas, the other relatively level and gently sloping areas of the site are currently covered by garden beds. The surface of the slopes above the existing house are sparsely grassed with a few trees, whilst below the house, the slopes are heavily grassed and are overgrown.

3.2 Subsurface Conditions

The subsurface conditions encountered in test holes and exposed in the cut slope above the existing building indicate that the subsurface conditions at the site generally consist of a layer of stiff silty sandy clay.

The existing building platform was apparently formed by cut and fill earthworks. The foundation conditions on the building platform should comprise primarily residual silty sandy clay with probably silty sandy clay fill material towards the western end of the platform.

Groundwater was not encountered in the test holes to the depths investigated.

4.0 ENGINEERING COMMENTS

4.1 General

It is understood that the proposed development comprises a two level building on the existing building platform. It is further understood that there are no major earth works proposed. Engineering comments regarding stability, cut and fill earthworks, retaining structures and footings are presented in the following sections.

4.2 Stability

No obvious signs of large scale instability was observed within the site during the walkover survey, although some small scale instability was observed in the cut batter to the east of the building platform.

It is considered that with the adoption of sound engineering practices relevant to hillside construction (ie. those outlined in the following sections), the proposed development is feasible from a geotechnical point of view and that the site following development should be stable. As is the case for all hillside developments in the Port Douglas area, some minor instability should be expected. This instability is expected to be in the form of relatively minor slips and slumps on locally steep slopes or unsupported batters during periods of prolonged rainfall.

4.3 Drainage

The stability of the site is highly dependent on the provision and maintenance of adequate drainage, Suggested drainage measures that should be implemented include the following:

- Concrete lined cut-off drains or similar measures to intercept run-off on the uphill side of
 the proposed building, along the crest of cut and fill batters, above retaining walls and
 along any access road.
- Provision of subsurface drainage behind retaining walls.

In addition to the above stormwater should be collected and discharged from the site via pipes or lined drains rather than be allowed to flow onto the ground

4.4 Cut and Fill Earthworks

It is understood that only minor cut and fill earthworks will be required on the existing building platform.

Fill materials may exist in the western edge of the existing platform. The quality and quantity of the fill material could not be assessed during the investigation due to the presence of the existing building at the time of the fieldwork. It is recommended that the fill materials be removed and re-compacted in accordance with the following procedures. The new fill batter should be limited to a maximum slope of 1V:2H and a height of 3 m. Batters which are steeper and/or higher than this should be supported by engineer designed retaining walls. Site preparation and earthworks procedures for filling should comprise the following:

- Strip and remove topsoil material greater than 150 mm in size, soil containing significant
 amounts of organic materials and debris materials resulting from demolition of the
 existing house;
- Excavate and stockpile existing fill suitable for replacement.
- Compact subgrade areas with a heavy roller to reveal soft or loose zones;
- Soft materials that can not be improved by compaction should be removed and replaced with engineered fill;

Place fill in uniform horizontal layers not exceeding 200 mm loose thickness and compact
to achieve a density ratio of at least 98% using Standard Compaction. Each layer should
be keyed into natural ground. Filling should be constructed beyond the design profile and
then trimmed to the design profile.

The insitu-natural materials and most of the existing fills are considered to be suitable for use as engineered fill. Compaction levels should be checked by field density testing during filling in accordance with AS3798-1996 – Guidelines on Earthworks for Commercial and Residential Development.

4.5 Retaining Structures

Retaining walls forming part of the buildings structure should be designed using an earth pressure coefficient of 0.6 for soils and engineered fill. For other retaining structures an earth pressure coefficient of 0.4 could be adopted. Due allowances should be made for any surcharge loads imposed on retaining walls. Footings for retaining walls should be founded at least 0.5 m into stiff silty sandy clay and can be designed using allowable bearing pressures up to 150 kPa.

4.6 Footings

Bored pier footings, if proposed, should extend at least 1 m into stiff silty sandy clay and can be designed using an allowable end bearing pressure of up to 200 kPa. If piers are adopted a side adhesion of up to 40 kPa may be adopted for uplift design, neglecting the contribution of the upper 1.0 m of soil.

Pad and strip footings in existing slopes should be keyed into the slope and founded at least 0.5 m into natural silty sandy clay. These footings may be designed for allowable bearing pressures of up to 100 kPa. Beams for slab-on-ground footings founded on cut surfaces and future engineered fill may be designed for allowable bearing pressures of up to 100 kPa.

Total settlement is estimated to be less than 10 mm for structures supported on bored piers and pad/strip footings founded in very stiff clays or stronger founding materials. However, total and differential settlement could be up to 20 mm for structures supported partially on cut and partially on engineered fill.

It is recommended that footing excavations be inspected by Golder Associates to confirm that founding conditions are consistent with those on which the design is based.

5.0 IMPORTANT INFORMATION

Your attention is drawn to the document - "Important Information About Your Geotechnical Engineering Report", which is included in Appendix C of this report. This document has been prepared by the ASFE (Professional Firms Practicing in the Geosciences), of which Golder Associates is a member. The statements presented in this document are intended to advise you of what your realistic expectations of this report should be, and to present you with recommendations on how to minimise the risks associated with the groundworks for this project. The document is not intended to reduce the level of responsibility accepted by Golder Associates, but rather to ensure that all parties who may rely on this report are aware of the responsibilities each assumes in so doing.

We would be pleased to answer any questions about this important information from the reader of this report.

GOLDER ASSOCIATES PTY LTD

10g bl

Kejing Chen

Senior Engineer

KC/MSC/eps

\GOLDERCNSVOBS\2GE004\04672000\TASK | - LOT 2 MURPHY STREET\72000-1RB.DOC

APPENDIX A RESULTS OF FIELDWORK



REPORT OF BOREHOLE: HA1

CLIENT:

Stephen Ariss

PROJECT:

Lot 2 Murphy Street

POSITION:

SURFACE RL: m DATUM: AHD71

DRILL RIG:

SHEET: 1 OF 1

DRILLER:

LOGGED: SRF

LOCATION: JOB NO:

Port Douglas 04672000-1

INCLINATION: -90°

HOLE DIA: mm HOLE DEPTH: 1.50 m

DATE: 21/1/04 CHECKED: K DATE: 20/104

,	<u> </u>	יו סל			04072		ROLE DIA. MIII HOLE DEPTH, 1.30 III CHECKED, PC DATE. 20/10/0						
i	_			ling		Sampling	+			Field Material Descri			
	METHOD	PENETRATION RESISTANCE	WATER		DEPTH RL	SAMPLE OR FIELD TEST		GRAPHIC LOG	USC Symbol	SOIL / ROCK MATERIAL DESCRIPTION	MOISTURE	CONSISTENCY DENSITY	STRUCTURE AND ADDITIONAL OBSERVATIONS
1				0.0			. Y	<u>17. 7.</u>	CL	TOPSOIL:- Sity Sandy CLAY Low plasticity, dark brown.		<u> </u>	
				-		DS 0.10-0.50m	2	77. 77. 12. 71		Low plasticity, dark prown.			
		L		-	0.30		ı,	: Mill	CL	Sitty Sandy CLAY			-
										Low plasticity, orange		İ	-
İ			-	0.5			ľ						-
	HA	м	untere	-			Ê	1			∑	ಹ	-
	I	IVI.	Enco	-	0,80		5			Some gravel and coarse sand.	•==	"	-
1			ar No	1.0			2	<u> </u>					
			Groundwater Not Encountered	-			-						-
1	ı	н	g	1			2	٠,					
				1			3	<u>:-/</u>					
-			-	1.5	1.50		-	- <u>-×</u>		HAND AUGER DISCONTINUED @ 1.5m			
١				1		.]				3			-
١			İ]							į		
١		ļ		-] -
				2.0									. -
İ			i]								ÌÌ	
	l		-	4				ļ					
30/01/2004 2:26:58 PM	Į		ĺ	-				İ					_
22.			ſ	2.5									-
01/200				4			1						-
				4	İ								-
ř.				3.0		•	ı						
Z.				J.J.									-
χ. 6			ļ	╡									-
Š				·]								l	
ELVZ				3.5	ł							ŀ	-
STRE				4	1								
E S]									
T2M				-			1						-
				4.0-			ļ						-
5 1.GLB FULL PAGE JACGEOGRANGT20NOTASK1 - LOT 2 MURPHY STREETV72000-1_EX2.GPJ GAPS_1:									ļ				
67200K				ļ					ļ				[]
204/04				4			-						-
142GE				4.5		İ							-
å GE				1	ļ	<u> </u>			ĺ				-
핅				4									-
8					Ī			-				-	-
				₽:0—							- –		

This report of borehole must be read in conjunction with accompanying notes and abbreviations. It has been prepared for geotechnical purposes only, without attempt to assess possible contamination. Any references to potential contamination are for information only and do not necessarily indicate the presence or absence of soil or groundwater contamination.

GAP gINT FN. F01a



REPORT OF BOREHOLE: HA2

CLIENT: PROJECT: Stephen Ariss

Lot 2 Murphy Street

POSITION:

SURFACE RL: m DATUM: AHD71

SHEET: 1 OF 1

DRILL RIG:

DRILLER:

LOGGED: SRF

DATE: 21/1/04

LOCATION: JOB NO:

Port Douglas 04672000-1

INCLINATION: -90°

HOLE DIA: mm HOLE DEPTH: 1.30 m

DATE: 30/1/04 CHECKED:

ŀ			Dt	iling		Complies		ī	Field Material Description					
ŀ				Hirig		Sampling	_	 	Γ.	Field Material Descr	i		·	
	METHOD	PENETRATION RESISTANCE	WATER		DEPTH RL	SAMPLE OR FIELD TEST	RECOVERED		USC Symbol	SOIL / ROCK MATERIAL DESCRIPTION	MOISTURE	CONSISTENCY	STRUCTURE AND ADDITIONAL OBSERVATIONS	
ı				0.0			Т	58.5	CL	TOPSOIL:- Sitty SAND, fine to medium grain, brown			l i	
			,	0.5	0.20			×	CL	Sitty Sandy CLAY Low plasticity, orange brown, some gravel				
اسب	Ą	M	Groundwater Not Encountered	5.3				×			Σ	\$\$	-	
		н	Groundw	1.0-	1.30			* · · · · · · · · · · · · · · · · · · ·		HAND AUGER DISCONTINUED @ 1.3m			-	
				1.5—						Due to Refusal			- - - -	
				20-									- - -	
0/01/2004 2/29:00 PM				2.5		·								
2.GPJ GAPS 1.		i		3.0									- - -	
1.GLB FULL PAGE JASGEOG4046720001/ASK 1 - LOT 2 MURPHY STREET72030-1 EX2.GPJ CAPS_1:				3.5—									1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
72000TASK 1 - LOT 2 MUI				4.0		į								
ULL PAGE J12GEOD4048				4.5									-	
1.0LB F		_		_5:8					_]					

This report of borehole must be read in conjunction with accompanying notes and abbreviations. It has been prepared for geotechnical purposes only, without attempt to assess possible contamination. Any references to potential contamination are for information only and do not necessarily indicate the presence or absence of soil or groundwater contamination.

GAP gINT FN. F01a RL2



REPORT OF BOREHOLE: EX1

CLIENT: PROJECT: Stephen Ariss

Lot 2 Murphy Street

POSITION:

SURFACE RL: m DATUM: AHD71

SHEET: 1 OF 1 DRILL RIG:

DRILLER: LOGGED: SRF

DATE: 21/1/04

LOCATION: JOB NO:

Port Douglas 04672000-1

INCLINATION: -90°

HOLE DIA: mm HOLE DEPTH: 2.00 m

CHECKED: DATE: 30/64

JOB NO: 04072000-1 ROLE DIA: IIIII ROLE DEPTH. 2.00 III CHECKLO. 177 DAT												
-	_			ling		Sampling	$\overline{}$	\vdash	Field Material Descri	_		 -
	METHOD	PENETRATION RESISTANCE	WATER		DEPTH RL	SAMPLE OR FIELD TEST	RECOVERED	GRAPHIC LOG	SOIL / ROCK MATERIAL DESCRIPTION	MOISTURE	CONSISTENCY DENSITY	STRUCTURE AND ADDITIONAL OBSERVATIONS
	EE		Groundwater Not Encountered	0.5		DS 1.50-1.60m		X	Sity Sandy CLAY Low plasticity, brown, some cobbles gravel		35	
				-	2.00			×				
5_1.01B FULL PAGE INGGEOOGGGGTZGGGTTASKT - LOT Z MURPHY STREETYZGGG- EXZ.GPJ GAPS_1:		THE PROPERTY AND ADDRESS OF THE PROPERTY ADDRESS OF THE PROPERTY AND ADDRESS OF THE PROPERTY ADDRESS OF THE PROPERTY AND ADDRESS OF THE PROPERTY ADDRE	TO THE RESERVE TO THE PERSON OF THE PERSON O	2.5					EXPOSURE DISCONTINUED @ 2.0m			

This report of borehole must be read in conjunction with accompanying notes and abbreviations. It has been prepared for geotechnical purposes only, without attempt to assess possible contamination. Any references to potential contamination are for information only and do not necessarily indicate the presence or absence of soil or groundwater contamination.

GAP gINT FN. F01a RL2



REPORT OF BOREHOLE: EX2

CLIENT:

LOCATION:

Stephen Ariss

PROJECT:

Lot 2 Murphy Street Port Douglas

POSITION:

SURFACE RL: m DATUM: AHD71

INCLINATION: -90°

SHEET: 1 OF 1

DRILL RIG:

DRILLER:

DATE: 21/1/04 LOGGED: SRF

		DCA DCA			POR D 04672				HOLE DIA: mm HOLE DEPTH: 4.00 m				CHECKED: LC DATE: 30/104			
·				lling		Sampling				Field Material Descri		n				
	METHOD	PENETRATION RESISTANCE		DEPTH (metres)	DEPTH RL	SAMPLE OR FIELD TEST	RECOVERED	GRAPHIC LOG	USC Symbol	SOIL / ROCK MATERIAL DESCRIPTION	MOISTURE	CONSISTENCY	STRUCTURE AND ADDITIONAL OBSERVATIONS			
PE_JOLB FULL PAGE JIGGEDOMGASTZOONTASK 1-LOT Z MURPHY STREETYZOOG-J EXZ.GPJ GAPS_1/ QUIZZOO4 220856 PM			Groundwater Not Encountered	1.5	4.00	This report of boreho	e	W. X. X. X. X. X. X. X. X. X. X. X. X. X.		Silty Sandy CLAY Low plasticity, brown Silty Sandy CLAY Low plasticity, orange EXPOSURE DISCONTINUED @ 4m	It h	D. D. D. D. D. D. D. D. D. D. D. D. D. D	een prepared for			

This report of borehole must be read in conjunction with accompanying notes and abbreviations. It has been prepared for geotechnical purposes only, without attempt to assess possible confarrination. Any references to potential contamination are for information only and do not necessarily indicate the presence or absence of soil or groundwater contamination.

GAP gINT FN. F01a RL2



METHOD OF SOIL DESCRIPTION USED ON BOREHOLE AND TEST PIT REPORTS

GRAPHIC LOG - TYPICAL SYMBOLS FOR SOILS

FILL

CLAY (CL, CLOR CH)

CRGANIC SOILS
(OL OR OH OR Pt)

COBBLES OR BOULDERS

🏅 🐧 SILT (ML OR MH)

Combinations of these basic symbols may be used to indicate mixed materials such as sandy clay.


CLASSIFICATION AND INFERRED STRATIGRAPHY

Soil and Rock is classified and described in Reports of Boreholes and Test Pits using the preferred method given in AS1726 - 1993, Appendix A. The material properties are assessed in the field by visual/tactile methods.

Particle Size

Major Division	Sub Division	Particle Size
BOULDERS		> 200 mm
COBBLES		63 to 200 mm
	Coarse	20 to 63 mm
GRAVEL	Medium	6.0 to 20 mm
	Fine	2,0 to 6.0 mm
	Coarse	0.6 to 2.0 mm
SAND	Medium	0.2 to 0.6 mm
	Fine	0.075 to 0.2 mm
SILT	•••	0.002 to 0.075 mm
CLAY		< 0.002 mm

Plasticity Properties



MOISTURE CONDITION

AS1726 - 1993

Symbol	Term	Description
D	Dry	Sands and gravels are free flowing. Clays & Slits may be brittle or friable and powdery.
М	Moist	Soils are darker than in the dry condition & may feel cool. Sands and gravels tend to cohere.
W	Wet	Soils exude free water. Sands and gravels tend to cohere.

CONSISTENCY AND DENSITY

AS1726 - 1993

Symbol	Term	Undrained Shear Strength	Symbol	Term	Density Index %	SPT "N" #
VS	Very Soft	0 to 12 kPa	VL	Very Loose	Less than 15	0 to 4
s	Soft	12 to 25 kPa	L	Loose	15 to 35	4 to 10
F	Firm .	25 to 50 kPa	MD	Medium Dense	35 to 65	10 to 30
St	Stiff	50 to 100 kPa	D	Dense	65 to 85	30 to 50
VSt	Very Stiff	100 to 200 kPa	VD	Very Dense	above 85	Above 50
Н	Hard	above 200 kPa	·			

[#] SPT correlations are not stated in AS1726 – 1993, and may be subject to corrections for overburden pressure and equipment type.

In the absence of test results, consistency and density may be assessed from correlations with the observed behaviour of the material.



EXPLANATION OF NOTES, ABBREVIATIONS & TERMS USED ON BOREHOLE AND TEST PIT REPORTS

DRILL	ING/EXCAVATION METHO	D			· -,-
AS*	Auger Screwing	RD	Rotary blade or drag bit	HQ	Diamond Core - 63 mm
AD*	Auger Drilling	RŢ	Rotary Tricone bit	NMLC	Diamond Core - 52 mm
*\/	V-Bit	RAB	Rotary Air Blast	NQ	Diamond Core - 47 mm
*T	TC-Bit, e.g. ADT	RC	Reverse Circulation	BH	Tractor Mounted Backhoe
HA	Hand Auger	PT	Push Tube	EX	Tracked Hydraulic Excavator
DTC	Diatube Coring	CT	Cable Tool Rig	EE	Existing Excavation
WB	Washbore or Bailer	JET	Jetting	HAND	Excavated by Hand Methods

PENETRATION/EXCAVATION RESISTANCE

- Low resistance. Rapid penetration possible with little effort from the equipment used.
- M Medium resistance. Excavation/possible at an acceptable rate with moderate effort from the equipment used.
- High resistance to penetration/excavation. Further penetration is possible at a slow rate and requires н significant effort from the equipment.
- Refusal or Practical Refusal. No further progress possible without the risk of damage or unacceptable wear to R the digging implement or machine.

These assessments are subjective and are dependent on many factors including the equipment power, weight, condition of excavation or drilling tools, and the experience of the operator.

۱۸	12	۲.	T	F	R
		٦.		_	

 ∇

Water level at date shown

Partial water loss

Complete water loss

Water inflow

GROUNDWATER NOT

OBSERVED

The observation of groundwater, whether present or not, was not possible due to drilling water, surface seepage or cave in of the borehole/test pit.

GROUNDWATER NOT

ENCOUNTERED

The borehole/test pit was dry soon after excavation. However, groundwater could be present in less permeable strata. Inflow may have been observed had the borehole/test pit

been left open for a longer period.

SAMPLING AND TESTING

SPT

Standard Penetration Test to AS1289,6,3,1-1993

4,7,11 N=18 30/80mm

4,7,11 = Blows per 150mm. N = Blows per 300mm penetration following 150mm seating Where practical refusal occurs, the blows and penetration for that interval are reported

Penetration occurred under the rod weight only RW

Penetration occurred under the hammer and rod weight only HW Hammer double bouncing on anvil

ΗB DS

BDS G

Disturbed sample Bulk disturbed sample

Gas Sample

Water Sample W Field permeability test over section noted FP

FV Field vane shear test expressed as uncorrected shear strength sy

Photoionisation Detector reading in ppm PID Pressuremeter test over section noted PM

PΡ Pocket penetrometer test expressed as instrument reading in kPa

Thin walled tube sample - number indicates nominal sample diameter in millimetres U63

Ranking of Vi	sually Observable Contamination and Odou	ır (for specific	soil contamination assessment projects)
R=0	No visible evidence of contamination	R≠A	No non-natural odours identified

11 - 0	140 VISIBIE EVIGENCE OF CONCERNIA IGNOR	I 13 - 13 .	140 Hon-Hattian daoare racintinos
R = 1	Slight evidence of visible contamination	R=B	Slight non-natural odours identified
R = 2	Visible contamination	R = C	Moderate non-natural odours identified
R=3	Significant visible contamination	R≖D	Strong non-natural odours identified

ROCK CORE RECOVERY

TCR = Total Core Recovery (%)

SCR = Solid Core Recovery (%)

RQD = Rock Quality Designation (%)

Length of core recovered × 100 Length of core run

 \sum Length of cylindrical core recovered Length of core run

 \sum Axial lengths of core > 100 mm \times 100 Length of core run

APPENDIX B RESULTS OF LABORATORY TESTING

Golder Associates Pty Ltd NORTH QUEENSLAND LABORATORY 216 Draper Street, CAIRNS, QLD, 4870 NATA Accreditation No: 3732



PARTICLE SIZE DISTRIBUTION & CONSISTENCY LIMITS TEST REPORT

Client Job Number 04672000-1 Client Address 8 Latitude, 16 Murphy Street, Port Douglas, Qld 4871 Date 30-Jan-04 Lot Murphy Street Project NQ-04018 Report Number Page No 1 of 1 Location Port Douglas Sampling Method As Supplied to Laboratory AH1 0.1-0.5m Lab Ref No. 04/024 Sample Identification Laboratory Specimen Description CL. Silty sandy CLAY, low plasticity, red brown. (AS1726, App A, Sect 2) PARTICLE SIZE DISTRIBUTION AS1289 3.6.1 CLASSIFICATION LIMITS AND MOISTURE CONTENT Spec, Spec. Spec. Spec. Lowe Sieve Size % Passing Test Method Result Upper Lower Upper 150 mm 100 Liquid Limit AS1289 3.1.2 30 100 നമ്പ 100 Plastic Limit % AS1289 3,2.1 17 75 mm 100 Plasticity Index % AS1289 3,3,1 13 53 mm 100 Linear Shrinkage % AS1289 3.4.1 ND AS1289 2.1.1 37.5 mm 100 Moisture Content 14.8 26.5 mm 100 Air dried Sample History: 19.0 mm 100 Preparation Method; Dry sieved 13.2 mm 100 Crumbling / Curling of Linear Shrinkage: 9.5 mm 100 Linear Shrinkage Mould Length; 6.7 mm 100 98 NP = non-plastic NO = not obtainable ND = not determined 4.75 mm 2.36 mm 95 1.18 mm 91 0.600mm 83 0.425mm 78 0.300mm 73 0.150mm 64 0.075mm 51 PARTICLE SIZE DISTRIBUTION 100 90 80 PERCENTAGE PASSING 70 60 50 40 30 20 10 Λ 0.001 0.01 0.1 10 100 PARTICLE SIZE (mm) SAND FRACTION GRAVEL FRACTION SILT FRACTION COBBLES BOULDERS MEDIUM MEDIUM COARSE MEDIUM

This laboratory is accredited by the National Association of Festing Authorities, Australia, The tests reported herein have been performed in accordance with its terms of accreditation.

THIS DOCUMENT SHALL ONLY BE REPRODUCED IN FULL

Darryl Murphy Laboratory-Mapager
AUTHORISED SIGNATORY

30-Jan-04 DATE

APPENDIX C

"IMPORTANT INFORMATION ABOUT YOUR GEOTECHNICAL ENGINEERING REPORT"

Important Information About Your

Geotechnical Engineering Report

Subsurface problems are a principal cause of construction delays,

The following information is provided to help you manage your risks.

Geotechnical Services Are Performed for Specific Purposes, Persons, and Projects

Geotechnical engineers structure their services to meet the specific needs of their clients. A geotechnical engineering study conducted for a civil engineer may not fulfil the needs of a construction contractor or even another civil engineer. Because each geotechnical engineering study is unique, each geotechnical engineering report is unique, prepared solely for the elient. No one except you should rely on your geotechnical engineering report without first conferring with the geotechnical engineer who prepared it. And no one—not even you—should apply the report for any purpose or project except the one originally contemplated.

A Geotechnical Engineering Report Is Based on A Unique Set of Project-Specific Factors

Geotechnical engineers consider a number of unique, project-specific factors when establishing the scope of a study. Typical factors include: the client's goals, objectives, and risk management preferences; the general nature of the structure involved, its size, and configuration; the location of the structure on the site; and other planned or existing site improvements, such as access roads, parking lots, and underground utilities. Unless the geotechnical engineer who conducted the study specifically indicates otherwise, do not rely on a geotechnical engineering report that was:

- not prepared for you,
- not prepared for your project.
- not prepared for the specific site explored, or
- completed before important project changes were made

Typical change that can crode the reliability of an existing geotechnical engineering report include those that affect.

- the function of the proposed structure, as when it's changed from a parking garage to an office building, or from a light industrial plant to a refrigerated warehouse.
- elevation, configuration, location, orientation, or weight of the proposed structure,
- composition of the design team, or
- project ownership.

As a general rule, always inform your geotechnical engineer of project changes – even minor ones – and request an assessment of their impact. Geotechnical Engineers cannot accept responsibility or liability for problems that occur because their reports do not consider developments of which they were not informed

Subsurface Conditions Can Change

A geotechnical engineering report is based on conditions that existed at the time the study was performed. Do not rely on a geotechnical engineering report whose adequacy may have been affected by the passage of time; by man-made events, such as construction on or adjacent to the site; or by natural events, such as floods, earthquakes, or groundwater fluctuations. Always contact the geotechnical engineer before applying the report to determine if it is still reliable. A minor amount of additional testing or analysis could prevent major problems.

Most Geotechnical Findings Are Professional Opinions

Site exploration identifies subsurface conditions only at those points where subsurface tests are conducted or samples are taken. Geotechnical engineers review field and laboratory data and then apply their professional judgement to render an opinion about subsurface conditions throughout the site. Actual subsurface conditions may differ – sometimes significantly – from those indicated in your report. Retaining the geotechnical engineer who developed your report to provide construction observation is the most effective method of managing the risks associated with unanticipated conditions.

A Report's Recommendations Are Not Final

Do not overrely on the construction recommendations included in your report. Those recommendations are not final, because geotechnical engineers develop them principally from judgement and opinion. Geotechnical engineers can finalise their recommendations only by observing actual subsurface conditions revealed during construction. The geotechnical engineer who developed your report cannot assume responsibility or liability for the report's recommendations if that engineer does not perform construction observation.

A Geotechnical Engineering Report Is Subject to Misinterpretation

Other design team members misinterpretation of geotechnical engineering reports has resulted in costly problems. Lower that risk by having your geotechnical engineer confer with appropriate members of the design team after submitting the report. Also retain your geotechnical engineer to review pertinent elements of the design team's plans and specifications. Contractors can also misinterpret a geotechnical engineering report. Reduce that risk by having your geotechnical engineer participate in prebid and preconstruction conferences, and by providing construction observation.

Do Not Redraw the Engineer's Logs

Geotechnical engineers prepare final boring and testing logs based upon their interpretation of field logs and laboratory data. To prevent errors or omissions, the logs included in a geotechnical engineering report should never be redrawn for inclusion in architectural or other design drawings. Only photographic or electronic reproduction is acceptable, but recognise that separating logs from the report can elevate risk.

Give Contractors a Complete Report and Guidance

Some owners and design professionals mistakenly believe they can make contractors liable for unanticipated subsurface conditions by limiting what they provide for bid preparation. To help prevent costly problems, give contractors the complete geotechnical engineering report, but preface it with a clearly written letter of transmittal. In that letter, advise contractors that the report was not prepared for purposes of bid development and that the report's accuracy is limited; encourage them to confer with the geotechnical engineer who prepared the report (a modest fee may be required) and/or to conduct additional study to obtain the specific types of information they need or prefer. A prebid conference can also be valuable. Be sure contractors have sufficient time to perform additional study. Only then might you be in a position to give contractors the best information available. to you, while requiring them to at least there some of the financial responsibilities stemming from unanticipated conditions.

Read Responsibility Provisions Closely

Some chents, design professionals, and contractors do not recognise that geotechnical engineering is far less exact than other engineering disciplines. This lack of understanding has created unrealistic expectations that have led to disappointments, claims, and disputes. To help reduce such risks, geotechnical engineers commonly molude a variety of explanatory provisions in their reports. Sometimes labelled "limitations", many of these provisions indicate where geotechnical engineers responsibilities begin and end, to help others recognise their own responsibilities and risks. Read these provisions closely. Ask questions. Your geotechnical engineer should respond fully and frankly.

Geoenvironmental Concerns Are Not Covered

The equipment, techniques, and personnel used to perform a geoenvironmental study differ significantly from those used to perform a geotechnical study. For that reason, a geotechnical engineering report does not usually relate any geoenvironmental fundings, conclusions, or recommendations, e.g., about the likelihood of encountering underground storage tanks or regulated contaminants. Unanticipated environmental problems have led to numerous project failures. If you have not yet obtained your own geoenvironmental information, ask your geotechnical consultant for risk management guidance. Do not rely on an environmental report prepared for someone else.

Rely on Your Geotechnical Engineer for Additional Assistance


Membership in ASFE exposes geotechnical engineers to a wide array of risk management techniques that can be of genuine benefit for everyone involved with a construction project. Confer with your ASFE member geotechnical engineer for more information.



8811 Colesylle Road Sylle G106 Silver Spring MD 20910 Telephone: 301-565-2733 Faasimile; 301-589-2017 email: info@asfe.org www.asfe.org


Copyright 1998 by ASFE, Inc. Unless ASFE grants written permission to do so, duplication of this document by any means whatsoever is expressly prohibited. Re-use of the wording in this document, in whole or in part, also is expressly prohibited, and may be done only with the express permission of ASFE or for purposes of review of scholarly research.

HGER06983.5M





1/4

--




1/1






CROSS SECTIONS THROUGH SITE



CROSS SECTIONS THROUGH SITE



CROSS SECTIONS THROUGH SITE

considing engineers & managers

22 Templeton Shreet
Gerdomate QLD 4985
Australia
Fix 1429 830 442
oral: Austriconau

polyor

LOT 2 MURPHY STREET
PORT DOUGLAS


The Manager Austriconau

1: 200 MAY14


The Manager Austriconau

1: 200 MAY14

14/5/30 9:37










LOT 2 MURPHY STREET PORT DOUGLAS

PL PL	KL	drawing ma
- MSC	14176	01
1: 200	MAY14	74. 14







1/3




CROSS SECTIONS THROUGH SITE




CROSS SECTIONS THROUGH SITE



CROSS SECTIONS THROUGH SITE




14/4/110 0.1



22 Tempiston Street Contentvale CLD 4685 Australia Ptc 0426 630 442 small; statificationals

LOT 2 MURPHY STREET PORT DOUGLAS

[PL	KL KL	Smile on
- MSC	14176	01
1: 200	MAY14	ruc. sn.




EDGE


EDGE

ROAD


171



CROSS SECTIONS THROUGH SITE



CROSS SECTIONS THROUGH SITE



CROSS SECTIONS THROUGH SITE

Consulting angineers is managers

22 Tomphism Street
Gordervals CLD 4985
Australia
Fix 0429 5300 442
Annal : 4 sept (Scannic connect)

LOT 2 MURPHY STREET
PORT DOUGLAS

PL KL Gorden M.

1: 200 MAY14

The first fixed

14/4/30 0.3

4/4