YOUR REF:
 1301 L01

 OUR REF:
 OP 282/2014 (429514)

2 October 2014

Jim Papas Civil Engineering Designer Pty Ltd P O Box 2347 MAREEBA QLD 4880

Attention: Mr Jim Papas

Dear Sir

#### DECISION NOTICE FOR OPERATIONAL WORKS OCEAN BREEZE STAGE 5B – (19 LOT SUBIVISION) -LOT 901 ON SP264287 – BARRABAL DRIVE, COOYA BEACH

Please find attached the relevant Decision Notice for the above Operational Works. Also find attached a 'Pre-Start' meeting template, which identifies the information that must be provided for Council approval, prior to the commencement of works.

The template also provides the Consulting Engineer with a format for conducting the meeting. An invitation to attend the meeting must be sent to Council's representative Michael Matthews on telephone number 07 4099 9475, giving at least five (5) working days notification if possible.

In addition to the Decision Notice, Council provides the following 'Advice Statement' which relates to issues that are relevant to the proposed works:

- 1. The design of landscape and lighting works are subject to separate agreement and must be submitted to Council, prior to the commencement of associated works; and
- 2. The Consulting Engineer is to present all contractors with a copy of this Decision Notice and the Council approved plans, prior to the commencement of works.

Should you require further information or assistance, please contact Michael Matthews, Project Engineer, on telephone 07 4099 9475.

Yours faithfully

Donna Graham Manager Development and Environment

Att

Copy: Administration Officer (Water & Waste) Manager Infrastructure Services 
 YOUR REF:
 1301 L01

 OUR REF:
 OP 282/2014 (429514)

24 September 2014

## DECISION NOTICE FOR OPERATIONAL WORKS OCEAN BREEZE STAGE 5B COOYA BEACH ROAD, BONNIE DOON

#### **PROPOSAL:**

Operational Works (Engineering) excluding Landscape and Lighting Works

**TYPE OF DEVELOPMENT:** Operational Work

**REAL PROPERTY DESCRIPTION:** Lot 901 on SP264287

**REFERRAL AGENCY CONDITIONS:** None applicable

**FURTHER DEVELOPMENT PERMITS OR APPROVALS REQUIRED:** Water and Waste Application for a Water Service Connection

## **DECISION DATE:**

2 October 2014

#### **DECISION:**

Approved subject to conditions

TYPE OF APPROVAL:

**Development Permit** 

## ASSESSMENT MANAGER CONDITIONS – STANDARD:

The standard conditions are shown in Appendix A and must be read in conjunction with any approved plans and project specific conditions identified below.

## ASSESSMENT MANAGER CONDITIONS – PROJECT SPECIFIC:

## 1. General

- a. This site shall be subject to regular inspections by Douglas Shire Councils' Officers.
- b. Any proposed work to be carried on the existing Telstra Pit is to be approved by Telstra.
- c. All existing services within the development area, including **Barrabal Drive**, must be pot-holed and levels confirmed prior to commencement of works.
- d. In the event that acid sulphate soils are encountered, the applicant is to ensure the site is managed in accordance with the requirements of the Potential Acid Sulfate Soil Investigation Report prepared by C&B Consultants (now RPS) for Salson Pty Ltd.
- e. Any existing Council infrastructure or private property (including but not limited to, services, kerb, concrete structures, pits, channels, pavement, footpath, RCP, RCBC, etc.) damaged due to the proposed works is to be rectified or replaced at the applicant's expense prior to the commencement of use. The applicant must notify Douglas Shire Council of the affected infrastructure.
- f. The applicant is to implement a Traffic/Pedestrian Management Plan in accordance with the Department of Main Roads Manual of Uniform Traffic Control Devices (Section 3 Works on Roads). A Risk Assessment is to be made taking particular account of factors such as traffic volume and speed, road geometry, width and surface conditions, and the general behaviour of road users and pedestrians. This plan is to be submitted **prior to the Pre-Start Meeting.**
- g. Considering that this area is a low wet site and may have a very poor subgrade, the applicant is to confirm with calculations based on Austroads – Pavement Design – A Guide to the Structural Design of Road Pavements - that the shown road pavement will be adequate for this location; otherwise, a suitable subgrade stabilisation method is to be included.
- h. The proposed 2.0m concrete footpath to be installed along Barrabal Drive is to be shown on drawing 1301-C04-Rev (A) - Typical Cross Section Detail. For consistence with previous infrastructure 1.5m concrete footpath to be extended to the intersection of Barrabal Drive and Road J.

i. The landscaping plan is to be provided **6 weeks** after the Pre-Start Meeting for approval.

# 2. Site Regrading

- a. Batters fronting Cooya Beach Road Reserve are not to be steeper than 1 in 4; otherwise, a retaining structure is to be implemented subject to approval by the Council.
- b. All earthworks are to be constructed in accordance with Australian Standard 3798-2007, Guidelines on Earthworks for Commercial and Residential Developments; additionally, further certification is to occur when works are completed and test results are compiled. This information is to be provided to Council **prior to Works Acceptance.**
- c. The works must not cause, or be likely to cause, environmental harm resulting from the release of contaminants, dust, noise or sediments from the site. Appropriate Erosion and Sediment Control (ESC) measures must be installed and maintained for the duration of the works or until all exposed areas have been fully re-vegetated or stabilized.
- d. Soil used for filling or spoil from the excavation is not to be stockpiled in locations that can be viewed from adjoining premises or within the road reserve for more than **1 month**, and the storage of any machinery, material and vehicles must not cause a nuisance to surrounding properties.

# 3. Stormwater & Drainage

a. All stormwater from the property must be directed to a lawful point of discharge such that it does not adversely affect surrounding properties or properties downstream from the development to the requirements and satisfaction of the Chief Executive Officer.

# 4. Erosion and Sediment Control

- a. In the event that dewatering is to be implemented on-site, the Contractor is to supply a dewatering plan for the project to Council prior to the commencement of dewatering operations, with the following details:
  - Preferred method
  - Proposed start / end dates of dewatering
  - Map showing the preferred site of any retention basin/s (if applicable)
  - Schedule of ongoing water quality monitoring (i.e. particularly of discharged water)
  - Proposed method of disposal and treatment (if necessary) of discharged water (including map showing discharge point)

44.2014.282 2/32

- The pH must be between 6.5 and 8.5 prior to discharge.
- b. **Prior to the Pre-Start Meeting** the applicant is to provide for approval, the Contractor Erosion and Sediment Control Plan (ESCP) together with drawings showing measures to be implemented on-site during construction, and the defect liability period. The drawings are to show the following activities:
  - Establishment to site
  - Clear and strip
  - Earthworks and
  - Completion of all works
- c. During construction the contractor must implement a suitable **Dust Management Strategy** to minimise dust nuisance on adjacent properties. Details of the dust management strategy must be incorporated into the erosion & sediment control strategy and be noted on the contractor's ESC plan.
- d. Upon completion of earthworks and **prior to Works Acceptance** all exposed surfaces are to be treated (i.e., drill seeding, hydromulching) to prevent erosion. Temporary ESC measures must remain in place during construction and until the site is stabilised to prevent sediment entering to any adjacent drain or properties around; additional ESC protection is to be installed at existing kerb inlets located in **Barrabal Drive.**
- e. All reasonable and practicable measures must be taken to prevent pollution to the existing creek, waterways or drainage lines, as a result of silt run-off, oil and grease spills from any machinery. Wastewater for cleaning equipment must not be discharged or in-directly to any watercourses, stormwater systems or private properties.

# 5. Sewer

- a. The Inspection and Test Plan must be approved prior to the pre-start meeting. At project completion the completed and validated ITP must be submitted and approved prior to the issue of a Works Acceptance Certificate.
- b. Easements must be registered over sewers where the depth to invert is greater than 3m.
- c. Minimum clearances between sewer mains and other services must be in accordance with the Sewerage Code of Australia.
- d. Where a manhole is located in a batter, a flat area of 1.5m radius from the centre of the manhole must be provided. Where the manhole is located along a side or rear boundary and is on the 0.8m standard alignment then the flat area must be on at least three sides. In particular a typical detail for how the flat area will be achieved must be approved prior to commencement of construction.

- e. Where an easement is required the property connection branch must be extended at least 1m from the easement boundary.
- f. House drains are to extend 1.5m beyond the top of batters.
- g. As-constructed sewerage drawings must be approved prior to granting of Early Plan Sealing or Issue of a Works Acceptance Certificate whichever occurs first. The As-constructed sewerage submission is to include the "Statement of Compliance – As-constructed Documentation" and must be the final issue.
- h. CCTV inspection must be carried out through all sewers constructed as part of this development and the Consultant is to assess the CCTV footage and prepare a report on the condition of as-constructed sewers. The report must be submitted and approved by Water and Waste prior to issue of Works Acceptance. Rectification of sub-standard sewers shall be carried out to the satisfaction of Council.

# 6. Water

- a. An additional scenario of the network model must be undertaken to verify the pressures for constructed stages and proposed stage 5A comply with the Development Manual. The boundary conditions for the scenario must reflect the current supply pressure determined in consultation with Council and is inprinciple the pressure available due to the interconnection of the 225ND trunk main in Bonnie Doon Road. A hydrant test at the developer's expense must be carried out at a suitable location in consultation with Council to validate the hydraulic analysis. The report of the additional modelling must be submitted for approval prior to commencement of water reticulation construction.
- b. The Inspection and Test Plan must be approved prior to the pre-start meeting. At project completion the completed and validated ITP must be submitted and approved prior to the issue of a Works Acceptance Certificate.
- c. Minimum clearances between water mains and other services must be in accordance with the Water Supply Code of Australia in particular the minimum clearance between water mains and sewer mains must be 500mm with the sewer under the water main.
- d. As-constructed water submissions are to include the "Statement of Compliance

   As-constructed Documentation" and must be the final issue. The asconstructed drawing must be approved prior to Issue of a Works Acceptance Certificate.

## 7. Lighting

a. Design to be submitted to Council for agreement.

## 10. Vegetation

44.2014.282 4/32 'The regrowth vegetation code clearing notification form should be forwarded to the Department of Environment and Heritage Protection prior to the clearing of any vegetation mapped as important regrowth under the *Vegetation Management Act* 1999.' 'Any clearing of important regrowth vegetation should be in accordance with the Regrowth Vegetation Code.'

Copies of the regrowth maps can be found at <u>www.ehp.qld.gov.au</u> .

### 11. Other

a. No comments.

## APPROVED PLANS AND SPECIFICATIONS:

Generally in accordance with the following drawings submitted by Jim Papas Civil Engineering Designer Pty Ltd subject to any alterations made by conditions of Development Permit for Operational Work OP 282/2014.

Drawing Description	No.	Rev.
Existing Site Plan	1301-C01	A
Typical Cross Section, Pavement Data, Set Out and Intersection Details	1301-C02	A
Bulk Earthworks Plan	1301-C03	Α
Earthworks, Roadworks and Stormwater Drainage Plan	1301-C04	A
Soil and Water Management Plan	1301-C05	A
Sewer Reticulation Plan	1301-C06	А
Water Reticulation Plan	1301-C07	A
Barrabal Road - Longitudinal Section	1301-C08	A
Barrabal Road - Cross Section	1301-C09	A
Road J – Longitudinal and Cross Sections	1301-C10	A
Stormwater Drainage – Longitudinal Section, Set Out Data, Pit Schedule and Notes	1301-C11	Α
Sewerage Reticulation – Longitudinal Sections, Set Out Data and Notes	1301-C12	Α
Stormwater Drainage Catchment Plan	1301-C13	A
Stormwater Drainage Calculation Sheet	1301-14	A


For information relating to the *Sustainable Planning Act* 2009 log on to <u>www.dsdip.qld.gov.au</u>. To access the *FNQROC Development Manual*, Local Laws and other applicable Policies log on to <u>www.douglas.qld.gov.au</u>.

RIGHTS OF APPEAL Attached


## **End of Decision Notice**


Att Appeal Rights Pre-Start Meeting Template Approved Drawings, Appendix A Standard Conditions, Appendix B


44.2014.282 6/32





Instantis     Instantis		Print and a particular state sources	DUTING OVER LINES	DOTHO TELETIA GALLES		5 DIZING SCHOOL	New Star subsc - a	THANKS BELORDER DATED			DISTNG CHARGE OF CONIC		IFIERD		REFERENCES.	THE COMPACT STATES AND THE ADDRESS AND THE COMPACT AND THE COMPACT STATES AND THE ADDRESS AND		A Head A		and Hard and A Links and	- Charlenge and the street score	· CHERI ENANDIN OF THE CONTRACT INVENION	PERSONAL WARES AND ANTIPACT TO ADDRESS THE	2. NOW TO BE COMPARISON OF CONSTRUCTION, NE CONTINUET IN TO EXPLANATION OF CONSTRUCTION, NEC	CONFLICTION OF THE INFORMATION SHOPS.	1. Entral Zenkes are nuted from the dest information and noted by the nuterior in the information and nuterior from the nuterior and	EDENVO SERVICES		LOGA ATHORY COUNCL	CONVEX OF SELVICES	NALESCORE.	THE ALL VERY MARKET WAS ADDRESS OF THE SAME THE	THE PRODUCT SUBCOME AND PRODUCT HIM.	THE CONTRACTOR TO CONTRA SURVEY ONLY WITH SUBSECTOR FROM TO CONDUCTOR OF WORK.	MIN	OVAXUE INTERNAL DEETING SAMPAGE Ovace INDEXTS AT 1.2m INTERNALS	NEWSON WILL DIVE 35	PSN 7038 WALLAN OFFICIAL	Here and the states and the sec	SURVEY CONTROL	NOTES
			5 1			87				5								i i i i i i i i i i i i i i i i i i i	i i i	8.8	55	6 6 8 8	83 6	IN THE	ŝ				10 10 10	NA LISL No.							`	N.	in the		1
DESIG	IN WE SHE WHE SHE	ATTA NO. ONE OWNER WA	ATTA NAME PART OF	CLIN (UD) SHE	and additional addition		1		AD AND AD	The set of the	CLIN OF SHE OF	Contraction of the	DOM NOT ON	International states		ADDRESS - 100 ADDRESS	( NOT)	Station of the second			DOM LINE SHE		ante ugos ante	4	Date: State (STATE)		D RE-Dis in	NUT STREET AND THE SHE	Contract and state law	ngit kii daa - sul, muqudi aan								Ĭ	1000	Ą	Ŋ
JIM PAPAS CIVIL ENGINEERING DESIGNER PTV. LTD. DESIGNER PTV. LTD.	8							-	5							9 1			1				27						_											Ż	$ _{i}$
S ERING (, LTD. Destroy		TO TO THE VIEW					-	111		5			_			-	10.0					· · ·		1 10			· · ·		North States	-1							j.	Z		]	İ
$\bigotimes$			The def set	THE OTHER PART	10 U D W	NOM / NO CLIMIT 1983	NACE SHOW CREEKE LOAN		5			C 201 MOT 1.4	HE NOW AD CARD WOY DA	NATIONAL PAR	물로	ē	A DID OVER CAME AND	all out date made say	AND		The set of the set of the set				HI HO OF ALL MADE AN AVE.		date and other passing sound		And used your law					Â	and a	Â					i
YOU											8		MOV CLA		HIN IS MUCH	+	ă	8	1	ŧ							NON-			×.		F	Ż	K		N.			all have		
VOU DIG	8 90.40	1 10	$\square$	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	-	-	1		-			Part & Define													بجري	5			K			Y.	ÿ			1	J	DAG /			
ူရန္က	AC 210 55 0000 10010 100100 501200	10110-01		C1 001100 1	A 144 CT 111 142 1440 04700	A 111 1 101 10 10 10 10 10 10	A the la serve strated and an	1074.05 NOLITE 4.30 25 NO 24 PM		a dicterior de	10441d17	North C	SHEAL AND A						يسا		990					F	E		田公					Ĭ		and pue loss	7	F	1	ļ	
	ALC: 10 10 10 10		ALC DOD VI CONT OF DIFFORM	NOV 10 10 10 10 10 10 10 10 10 10 10 10 10	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	00 31 111 1	Cite is and	50 20 100	100 100		2778 25 9960	La Sector	E.S.	,				NY.						rol	10	2		C				K	Ħ		Į	N III	N-ONO	and the party of t	No an	122	:
$\square$		1	2	<b>"</b>	1	_		ĩ			Ш					学行時	F	がい	SH	1. †	Ĵ,			$\overset{\times}{}$	7	6	1			1	Ę	H	L	6	湯辺	1	ľ	100	1		
"Ocean Breeze Estate" STAE 56 OF PROPOSED RESIDEMAL SUBONISION AT BARRADAL DRNE, COOMA BEACH SWARSTILE BLAK JE FM			INCOME OF DEEL		- LOSS OF DANKE TO THE WORKS	ALL DE NEWER AT NUMBER	nither ender name and architecture land	I'M SN	2. THERE WAS DEED TAM.		THE CONTINUES SALL PRODUCE THE FULLOWS	Min-State Harmes			MELALEUCA DAMA	推測的ななななない。「「」」」「「」、「」、「」、「」、「」、「」、「」、「」、「」、「」、」、、、、、、		いいいましたいというでものでした	する人に見たけにあたいたまでや		いていたが、これには、「ない」で、	のこうでは、「「「「」」」」」」」」」」」」」」」」」」」」」」」」」」」」」」」」」				いたいこれがたいとうなみまでに、	の一般にいたのないない	新になっ、「おうながのに通知が加加加」			AND							Add an			
V         Line         Li	50, 50, 6 , 7 , 8 , 8 , 90																	12	2 × 2	STACE 2	a de terrester a de la d		a					A start			\$.				-		PALM 87				

























arrierdensets - Galacit Mail für Hotolical, minist sommen.		CHANNE	ROAD CHAINAGE (CHFISET)	Several and a second	OF DRAIN	DEPTH OF HIGH	AT GRADE (Among	PIPE FLOW	Same Taylor Hudening	WATER LEVEL N 3	Weit The Part of t	PPE SLUCE I IN X PPE SLUCE I IN X PLL. PPE RAW VELOTIV INVA		STRUCTURE STRUCT
			(2009)		5,329	90	e.	e	4,980					
DESI		1.18	NUC	4294	2,41	140	1.03	101	4,504	4387	VATUM RL -2.0	SUD -		NERS PT ON GRADE 4/91
JIM PAPAS CIVIL ENGINEERING DESIGNER PTY, LTD. An Andrew Statements Statements An Andrew Statements Statements	Ę	10.79	12038	474	300 300	508 508 508	Unt	5	4480	4.05	<u> </u>	100 H	;	CITE Refease) Site of the second sec
PAPAS GINEERING R PTY, LTD.	LINE 61	ě.	130.07	4.672		1288	105	ŝ		1845				
ING.		4529	(160)	-unit	NH KH	1268			1,415	1,015			1	1 FORM PLAT (CRA)
$\bigotimes$		ŧs					шe	ç				without the		Example of the second s
YO														
VOU DIG		8,50 6 16,50		4,550	276 276 271	506 506	144	un	3,625	5,007		1900 I	1	CARENO STUDE
<b>۳</b>									1.56					
"Ocean Breeze Estat STACE SE OF HEORISED RESD AT BARADEL DRIVE, COOM BE MARE THE STANTE MARE LIGHT				and and sheet	DH1 BRMB PLUTT M GH6 SHRLL (JR/R), SHR 1994 MAAROLE TO FM04000	TWIS CONT	APPENDENCE NOT THE PARTY OF THE	NN TYPE N						Number         STRANAMER         S
Breeze Estate"     presze (state")       oF PROPOSED RESIDENTIL SUBDIVISION     presz (state")       SZERTE SMART, LINTICAL SET OF DATA STEDUC 40 KEE     presz (state")	904 100 M				440         500         31152         A118         5000         3.111         4.012           1952         4153         4.777         5000         3.115         4.012	aure (20ac aure ithue ou	Church Column	DV/DLY F3U	PIT SCHEDULS		STORMMATER DRAINAGE SET OUT DETAILS	ILANDIA UNTRI - LANDI MARELAN UNTRI - LANDI MAREL UNTRI - LANDI		MILE       Value       Value <tr< th=""></tr<>
C         Max         Max <thmax< th=""> <thmax< th=""> <thmax< th=""></thmax<></thmax<></thmax<>	902110 <mark>12 5 5 15 15 1</mark> 00 902110 <b>12 5 5 15 15 10</b>				ŝ	CH I	S	DEPTH DEPTH						In count In count Wideward Widewa





A manufactory and a manufactor					_								- 1-	1		٦
		8-	8- 8-	8×	8-	8-	8*	1×	8-	8=	8×	8- -	8-1		H	
		6	8	1	1	Ŕ	•		,		•	3	8	ansucture to	1	
		100	1400 NAY	No.	NUM S	A LOCAL	¥ 100	E.	÷.	1 a	100	1100	100	SAMPLE UTA	00000	2
		And a state of the	ALLER VIELS	8	ALC: NO.	VEX	No. of the local sector	and and an other	and the second	and a	5	10000	100	лан сограните сонтиратис		
	1	66	55 55	- 66	66	- 66	-	ĸ	55	£6	55	66	- 91	THE OF OTWO	÷	
	82	82	#S #S	62	12	17	82	82	82	12	82	22	52	SHEAL NORTH	F),	t.
	Dated and		1555 E5 1555 E5	95 95	55 55	55	55 55		55	22 22	55 55	22	55	CLEAR DEAL DATE OF BARRIES	C A	4. · · · · · · · · · · · · · · · · · · ·
89	Sec.		111 E	- 90 20	55	55	55		55	55	55	55	88	I INFAURTAIN	2	
JIM PAPAS CIVIL ENGINEERING DESUGATER FUEL DESUGATER FUEL AND THE SALAH TO	8		5 5 65	16	55	55	55	5 5	55	55	55	85			ê	
JIM PAPAS L ENGINEER GNIER PTY.	a firmer	1	ğ10 _ğ10	ĝ2+	A#	NES.	-	204 0	"ğrı	.ja.	.ğze	2.5	9.5	AND CATCHING THE REPORT	۰	
A PARA	2	-	N N	2 8	100	1		20	-	ii.				FLOR NALC (NC INPALE)	Ц	
TRING TRING		<u>د</u>		20	Contra to	100 m	6	2.5	100	15 5	1 E	5		KAD SAADE AT RAIT BINOR FLAN READ CAPACITY	Н	
19 2			5										-		1000	
			5 ·	ŝ	-		-	6						Harrine Koekrokan	8	2
<b>3</b>		-					-	-		F.	a a		- 1		e e	
		$\vdash$		3	8	8				1		1	3	STRUCTURE SIL	Ħ	
<b>K</b> 9		55	33 55	20 00	25 55	ee.	66	ść	66	1 <u>1</u> 51cc	66	66		STRUCTURE IN THE OF COLO	Ŧ	-
VOU DIG		ére gia	10 88 11 12	112	100 111	#2	20	52	62	Negation and a second	82	55 86	51	Life Ductor	H	
		55	55 55		56	55	16	55	55	155	15	55	-	Total, dr. e.	ė	
23		3	¥	ź	1	ŝ	8		I	1.	ž	ŧ			e	
์ ดี 🦹	0	_	6					3	Ŷ	IT.	2			BADY NUMACE IN OUR OWNER	5 3	8
	CALCULATIONS TABLE	- E	<u> </u>		-	1	I	f	F		26	Į	1	BADROLWASH.OF	0.000	
	Allo	20 20	20 22 20 22	10	10 10 10	0.000	-	24 24	10	1 14	10	1	72 84	Mesican Maciumen	*	
	NS TA		<u> </u>	ş			1	1	1.		E.			- He avor	-	
	316	â	8 8	1	ii ii	Dist.	8	R	8	8	N.	5	3	MENERAL (SLARS)	Π	
		101	3	12	No.	600 1 1000	(US)	R.	500	S.	S	s	12		ĸ	
48 d		<u>S</u>	<u><u><u></u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u></u>	ŝ	ŝ	5	5	÷.	5	5	5	ŝ	ŝ	TREOFICEN		4
"Ocean Breeze Estate" STARE SH OF PROPOSED RESIDEMAL AT BARRABAL DRME, COOMA BEACH		The Mandelson M and M	And a state of the state	panal in Los nues dell'investigo Lidentesia habite Ud et Invest fera Direction de	Southers for the points of the state of the souther the point through the souther the point through the	Spinite Science Spinite Services Version Spinite Spinite Version Spinite Net Sciences Spinite	ALCONG DALEASY DAVID TALEASY AND ALCONG DALEASY ALCONG DALEASY AND ALCONG DALEASY ALCONG DALEASY AND ALCONG DALEASY ALCONG DALEASY AND ALCONG DALEASY	De file a file efferte file Constante en la constant De file a constante en la constante Constante en la constante en la constante Constante en la constante en la constante en la constante Constante en la constante en la constante en la constante Constante en la constante en la constante en la constante en la constan	<ul> <li>A set of the set of</li></ul>	A contract of the contract on	A construction of the Cut of the cut of the Cut of the cut of the Cut of the cut of the Cut	<ul> <li>Appendix on Long Strategy</li> <li>Appen</li></ul>	parametria (Lenin A. 199) Sant' Marandogan (Lenin A. 199) Antonia - Chillenni Han (Lini Antonia - Chillenni Han (Lini Antonia - Chillenni Han (Lini	STRUCTURE AND A THE		
80 m		\$	5 5	5	s	5	5	6	5	5	5	5	5	VILSITYHIA	з.	
A B		5	5 5	5	5	5	E	5	6	5	5	5	5	NO HEADYOED	č i	L-1 10
DENTAL		5	<u>s</u> 6	ŝ	ę	ŝ	F	ş	£	ş	£	5		35 MPE 179457. 9040.055	r <sup>s</sup>	·
		2007	2007		193									CORRECT THE CORREC	-	
NOFINGERS		A A A A A A A A A A A A A A A A A A A	ALL DATE	10.00	And and	and the state	£	ş	State of the	1996 B	e	Contraction of the second seco	Street.		a a	
No.		19	8 28	-	19	*	5		- 12 · 1	100 C	5	1 220	1.		a a	
2			c 6		1 6	5	E		5	5	5	5	ę,		÷	
		2	5 5	ŝ	5	N.	5	ş	ŝ	5	£.	ş	ę,	#040.0551.10	-	
				Page 1		Number of Street									104	Ē
			<i>22</i> 22	184 184 185	22	N mil				22		5 g 6 c			Ŧ	4
		55 55	55 55		No.	50	SH SH	督督	55	55 65	55	55 55	经。	awar uvua Dagaacraa VAL	H.	
2 2		S S	10 12 E 5	52	80	18	10	si c	52	88 6	5	35	5 - S	WEIRAR NOL	H	
December 1 Million 1 December 1 D		8	5 5	ş	5	ŝ	-	5	5	= S	-	5	5	W.U.	H	6
		ŝ	<u>e</u> 8	ŝ	ŝ	5	5	ŝ	8	ŝ	5	1	ş,	Intervention mach	Н	
		10	and in	101	THE	8		4	5	9	ş	5	101	or RUCTURE No.	Π	
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		<u> </u>														-

## APPENDIX B: STANDARD CONDITIONS

## General

- 1. The proposed works are permitted subject to any alterations:
  - a. found necessary by Chief Executive Officer at the time of examination of Engineering drawings or during construction of the works because of particular engineering requirements and.
  - b. to ensure the works comply in all respects with the requirements of the *FNQROC Development Manual* and good engineering practice; and
  - c. to comply with project specific conditions and the following standard conditions of approval.

All works must be carried out in accordance with the approved plans, conditions and specifications, to the requirements and satisfaction of the Chief Executive Officer.

- 2. The conditions of any Reconfiguration of Lot or Material Change of Use permits applicable to the subject lot or lots shall be complied with in conjunction with this development permit.
- 3. Council's examination of the documents should not be taken to mean that the documents have been checked in detail and Council takes no responsibility for their accuracy. If during construction, inadequacies of the design are discovered, it is the responsibility of the Principal Consulting Engineer to resubmit amended plans to Council for approval and rectify works accordingly.
- 4. Notwithstanding any approval given to engineering documents, where a discrepancy occurs between these documents and Council's standards, then Council's standards shall apply. All works must be performed in accordance with Council standards and Local Laws and other statutory requirements.
- 5. If in fact there are errors, omissions or insufficient detail on the plans for the purpose of construction, these deficiencies shall be made good during construction and Council reserves the right to withhold approval of construction until such deficiencies are made good to its satisfaction.
- 6. Work and or Technical Documents identified within these Development Approval Conditions are nominated as requiring Compliance Assessment under section 398 of the *Sustainable Planning Act* 2009. In particular As-Constructed Water, Stormwater and Sewerage Plans must be submitted to the Compliance Assessor (Douglas Shire Council) on the approved form (Form 32) and will be assessed against the provisions of Council's *FNQROC Development Manual*. Council must issue a Compliance Certificate for the assessable documents prior to granting Early Plan Sealing or Plan Sealing of a Subdivision Plan or the issue of a Works Acceptance Certificate, whichever occurs first.

## Timing of Effect

7. The conditions of this development permit must be effected prior to the approval and dating of the survey plan, except where specified otherwise in these conditions of approval, or at Council's discretion.

### Easement Documentation

8. Easement documents are to be submitted to Council's solicitors for checking in accordance with the conditions of the Reconfiguration Development Permit. Contact Council for current nominated solicitors details.

### Portable Long Service Leave Notification

9. As per the QLeave – Building and Construction Industry Authority Guidelines, if the works are over \$80 000, Council must sight a copy of the receipted Portable Long Service Notification and Payment form prior to commencement of work.

### **Construction Security Bond**

10. Lodgement of Construction Security Bond as per the *FNQROC Development Manual*, Section CP1.07, (ie, five (5) per cent of the value of the works) is required, prior to commencement of work. The bond shall be in favour of Council and in the format of cash or an unconditional bank guarantee, which must cover all aspects of the construction and have no termination date.

### Third Party Agreement

11. The developer must obtain written agreement from third parties and/or Referral Agencies for any works proposed on adjacent properties. The agreement(s) must be provided prior to the associated works commencing on site. All agreements must be available for Council scrutiny, upon request.

#### **Commencement of Works**

12. Council is to receive written Notice of Intention to Commence Works and all matters relevant to the Pre-Start meeting are to be attended to in accordance with Section CP1.07, CP1.08 and Section CP1.09, of the *FNQROC Development Manual*.

## Hours of Work

- 13. Work involving the operation of construction plant and equipment of any description, shall only be carried out on site during the following times:
  - a. 7:00 am to 6:00 pm, Monday to Friday;
  - b. 7:00 am to 1:00 pm, Saturdays; and
  - c. no work is permitted on Sundays or Public Holidays.

Any variations to the above working hours must be authorised by the Chief Executive Officer, prior to the commencement of such works.

#### Public Notification of the Works

- 14. The developer or the nominated representative must provide:
  - a. Public notification of the development in local newspapers in accordance with Section CP1.11 of the *FNQROC Development Manual*.

b. Signage identifying the location of the project, general allotment layout, contact numbers (including out-of-office hours emergency numbers) must be provided at all entrance points to the development. All signage must be appropriately positioned, prior to the commencement of any works on the site.

## Site Inspections

15. Council requires a number of major inspections to be completed as Witness and Hold Points for Consulting Engineers and Council officers during the construction of the works. Inspections undertaken during construction shall be in accordance with Section CP1.16 (Inspection and Testing) of the *FNQROC Development Manual*. These Witness and Hold points are to be included in the contractors Inspection and Test Plan (ITP) and be made available for inspection, prior to the commencement of any works on the site.

## Soil and Water Management

- 16. All works must be in accordance with Section CP1.13 and D5 of the *FNQROC Development Manual,* and must comply with the following:
  - a. A copy of the contractor's Erosion and Sediment Control (ESC) Plan is to be submitted to Council and endorsed by the Consulting Engineer, prior to commencement of any works. In particular, the ESC Plan must address the Institution of Engineers' Australia *Guidelines for Soil Erosion and Sediment Control and the Environment Protection (Water) Policy* and Clauses CP1.06, CP1.13 and D5.10 of Council's *FNQROC Development Manual*. The ESC Plan must be relevant to <u>all phases</u> of the construction and be updated where necessary as works progress.
  - b. Any dewatering activities will require approval from Council's Environmental Protection Unit, telephone number 07 4099 9475 and a valid permit obtained prior to commencement.
  - c. During the construction period, the Consulting Engineer shall randomly audit and inspect ESC measures for compliance with the Engineer endorsed contractor's ESC Plan, derived from the Engineer's ESC Strategy (As per *FNQROC Development Manual* CP1 Appendix A).
  - d. It is the contractor's responsibility to ensure that the ESC Plan is updated and amended to reflect any changes in the construction methodology. All such amendments shall be approved by the Engineer and presented to Council.
  - e. The developer shall be held responsible for any rectification works required to clean up dust, pollutants and sediments that may leave the site as a result of construction activities.
  - f. The developer or their representative shall be responsible for communicating with third parties affected by any dust, pollutants or sediment leaving the site as a result of any construction activity that is associated with the project site.

## Street Lighting

17. The provision of street lighting is to be in accordance with the *FNQROC Development Manual* D8 and designed to comply with the Road Lighting Standard AS/NZS 1158, a compliance certificate that has been certified by an appropriate Registered Professional Engineer of Queensland (RPEQ) must be provided to demonstrate the lighting design complies to the requirements of the Road Lighting Standard AS/NZS 1158. New street lighting is to be erected as a Rate 2 public lighting installation, Rate 1 will only be considered where an overhead electricity reticulation exists:

- a. Lighting columns, luminaires and lamps are to be of a type specified in Ergon Energy's *Lighting Construction Manual*, unless approved otherwise by Council.
- b. The applicable lighting category for roads associated with this project having a road hierarchy of residential access and above is identified in Table D8.1 of the *FNQROC Development Manual.*
- c. Local Area Traffic Management (LATM) devices including roundabouts, must be provided with an illumination of not less than 3.5 Lux as specified in the Road Lighting Standard AS/NZS 1158.
- d. Street lighting located adjacent to the development frontage must be located behind the kerb (usually a minimum of 820 mm from the invert of the kerb) and spaced to meet the required lighting category for the road.

## Infrastructure Plans for Utility Services

18. Approved infrastructure plans for gas, electrical and telecommunications services must be endorsed by Council, prior to the commencement of associated works.

### Landscaping General

- 19. Landscaping shall be provided in accordance with Part D9 and Part S8 of the *FNQROC Development Manual*, unless approved otherwise by Council.
- 20. The landscaping works must be constructed in accordance with the approved plans and conditions. The developer must seek approval in writing from the Council for any changes to the plan or the landscaping works on the site. This approval must be obtained prior to commencement of these works on site.
- 21. The landscape must be maintained in good order by the developer for at least three (3) months during the Works Acceptance period, and generally timed to coincide with the Final Works Acceptance Inspection, when all landscaping works must be in a condition suitable for Council to commence regular maintenance.

#### Trees

- 22. Any trees must be planted and staked in accordance with the *FNQROC Development Manual* drawing S4210, with root barriers installed such that they are just visible at the finished surface level. Note that where footpaths are to be provided, a root barrier must also be provided between the tree and the path. Root barriers must be installed and appropriate topsoil, level of compaction and drainage provided, as specified by the manufacturer.
- 23. Street tree planting locations must be in compliance with *FNQROC Development Manual* D9.07.6 'Alignment and placement of Street Trees'. Trees shall be positioned a minimum of:
  - a. 7.5 metres from streetlights;
  - b. two (2) metres from the inlet or outlet of stormwater pipes;

- c, three (3) metres from any driveways;
- d. ten (10) metres back from the apex of both boundaries of a corner lot;
- e. 0.8 metres one (1) metres from the back of kerbs.
- 24. All trees must be watered directly after planting and prior to laying mulch. The mulch must be left clear of the trunk and be laid in accordance with *FNQROC Development Manual* drawing S4210 and S8.14, at a radius of 0.5 metre around the base of the tree and out to the back of kerb.
- 25. All trees must be of good vigour and health and must not be root-bound at the time of planting. They should be approximately 1.5 metres two (2) metres tall with well-established root and branch formation. Trees should have a clear dominant central leader.
- 26. A joint site inspection is to be held with Council officers and developer's representative to assess the general condition of any existing trees and shrubs within six (6) metres of any property boundary abutting the road reserve, or other Council land. If any dead, dying or dangerous trees are identified during the meeting, with the landowner's consent, they are to be removed to the satisfaction of Council officers, prior to the sealing of plans for the associated lot.
- 27. Any trees identified on drawings to be retained, are to be protected in accordance with approved plans. This must include, but is not limited to, the erection and continued maintenance of suitable physical barrier(s) placed around the tree to protect the tree and the root system. Additional protection of tree trunks by the fixing of timber planks using wire loops is also required unless approved otherwise by Council. Any damage caused to nominated trees as a result of construction activity, will require inspection by Council and will require a specified number of suitable replacements trees of suitable maturity to be provided to replace the loss in amenity.

# Verges

- 28. All verges are to be covered full-width with topsoil (AS 4419/Soils for Landscaping and Garden Use) to a depth of not less than 40 mm, lightly compacted and grassed in accordance with Council's Guidelines and Specifications.
- 29. Any island beds or any shrub beds must have a permanent irrigation system installed, which must be connected to the Douglas Water Network. An Application for a Water Service Connection must be presented to Douglas Water & Waste to facilitate the connection, and must include the installation of a flow meter and associated valves.
- 30. All water reticulation, including permanent irrigation systems, are to be identified in asconstructed plans which must be submitted to Council for approval prior to the Works Acceptance (On Maintenance) meeting for landscaping.

## **Structures and Retaining Walls**

31. Separate building certification and/or structural certification is required for any works to alter existing structures, provide new structures or construct retaining walls that are over 900 mm high. Certification by a suitably qualified engineer must be provided, prior to opening the work site to the public.

# The Location of Stormwater Quality Interception Devices (SQIDs)

44.2014.282 20/32 32. Council must approve the location of any SQIDs prior to installation. They shall be positioned to allow for economic and efficient maintenance operations, and will require a reinforced concrete hard standing area to be provided from the edge of the carriageway to the SQID location. Vehicular access from the public road reserve to the SQID must remain unrestricted.

## Sewer and Water

- 33. All water and sewerage works must be in accordance with Sections D6 and D7 of the *FNQROC Development Manual*, and must comply with the following:
  - a. Douglas Shire Council requires a minimum of five (5) working days notice of intention to commence water and sewerage related works. The notice shall be given to the Senior Plumbing Inspector at Douglas Shire Council either in writing, by telephone 07 4099 9479, fax 07 4098 2902 or email to enquiries@douglas.gld.gov.au prior to the commencement of works.
  - b. The developer shall be responsible for confirming the location of all existing sewer, water and utility service infrastructure prior to the commencement of works on site. Any permits necessary to alter/interfere with such services must be obtained prior to the commencement of work and be available for Council inspection if required.
  - c. Any works over or within the zone of influence of Council's existing water and sewerage infrastructure must be approved by Douglas Shire Council prior to the commencement of the proposed works. Unless otherwise approved in writing, existing infrastructure impacted by the development shall be subject to the maintenance period provisions contained in this Decision Notice.

Construction works shall include any works that may impact on existing infrastructure such as, but not limited to, mobilisation of heavy earthmoving equipment, stripping and grubbing, site filling, stockpiling of materials and installation of erosion and sediment control measures.

d. All testing and acceptance of water and sewerage works shall be in accordance with CP1 Construction Procedures of the *FNQROC Development Manual*. Works are to be certified as acceptable by Douglas Water & Waste, and any operating manuals etc be provided to Council, prior to making an application for the acceptance of the works.

## Sewer

- 34. Douglas Water & Waste must be contacted to perform any direct connection to live sewer mains. Unless otherwise approved in writing, separate applications for approval on the prescribed forms shall be made to Douglas Water & Waste for each connection together with payment of the relevant fee. All connections are to be provided subject to the terms and conditions of Douglas Shire Council's 'Application for Plumbing Works'.
  - a. Amended drawings in accordance with these conditions must be approved prior to the pre-start meeting.
  - b. The Inspection and Test Plan (ITP) must be approved prior to the pre-start meeting. At project completion the completed and validated ITP must be submitted and approved prior to the issue of a Works Acceptance Certificate.
  - c. Where retaining walls are located within the zone of influence of a sewer the footings must be 1000 mm clear of the sewer and designed in accordance with the

*Queensland Development Code*. Full design details and structural certification must be approved prior to commencement of works.

- d. Minimum clearances between sewer mains and other services must be in accordance with the *Sewerage Code of Australia*. Clearances must be included on the long-section drawing.
- e. Where a manhole is located in a batter, a flat area of 1.5 metres radius from the centre of the manhole must be provided. Where the manhole is located along a side or rear boundary and is on the 0.8 metre standard alignment then the flat area must be on at least three (3) sides.
- f. Where an easement is required the property connection branch must be extended at least one (1) metre from the easement boundary.
- g. House drains are to extend one (1) metre past the end of the driveway on hatchet blocks and 1.5 metres beyond the top of batters. An I.O. is to be provided at the downstream end of the house drain within one (1) metre of the boundary to delineate the end of the property connection branch.
- h. As-constructed sewerage drawings must be approved prior to granting of Early Plan Sealing or Issue of a Works Acceptance Certificate whichever occurs first. The as-constructed submission is to include the 'Statement of Compliance As-constructed Documentation' and must be the final issue.

### Water

- 35. Douglas Shire Council must be contacted to perform any direct connection to live water mains whether being as a permanent connection, a connection for irrigation purposes or for construction water. Unless otherwise approved in writing, separate applications on the prescribed forms shall be made to Douglas Shire Council for connections, together with payment of the relevant fee. All connections are to be provided subject to the terms and conditions of Douglas Shire Council's 'Application for a Water Service Connection'.
  - a. Amended drawings in accordance with these conditions must be approved prior to the pre-start meeting.
  - b. The Inspection and Test Plan (ITP) must be approved prior to the pre-start meeting. At project completion the completed and validated ITP must be submitted and approved prior to the issue of a Works Acceptance Certificate.
  - c. Minimum clearances between water mains and other services must be in accordance with the *Water Supply Code of Australia* in particular the minimum clearance between water mains and sewer mains must be 500 mm with the sewer under the water main.
  - d. As-constructed water drawings must be approved prior to Issue of a Works Acceptance Certificate. The as-constructed submission is to include the 'Statement of Compliance – As-constructed Documentation' and must be the final issue.

#### Roads and Footpaths

36. All works are to be designed and constructed in accordance with AS 1428.1-2001: 'Design for access and mobility' – General requirements for access – New building work, and associated standard AS/NZS 1428.4 2002, 'Design for Access and Mobility' – Tactile Indicators. The design is required to provide equal access for people with disability and include the provision of suitable ramps and landing areas and the installation of Tactile Ground Surface Indicators (TGSIs) where required.

## Cultural Heritage

37. The Aboriginal Cultural Heritage Act 2003 (the Act) seeks to protect artefacts and cultural sites that are of significance to Aboriginal people. The Act requires anyone carrying out an activity to exercise a Duty of Care. Guidelines have been produced to enable assessment of sites under the Act. These are available from Department of Environment Heritage Protection and can be downloaded from their website at <u>www.ehp.qld.gov.au</u>. The work identified in the project documentation is likely to require assessment of the site under the Act.